

CableLabs® Specifications

CableLabs' Assigned Names and Numbers

CL-SP-CANN-I16-170510

ISSUED

Notice

This CableLabs® specification is the result of a cooperative effort undertaken at the direction of Cable Television Laboratories, Inc. for the benefit of the cable industry and its customers. You may download, copy, distribute, and reference the documents herein only for the purpose of developing products or services in accordance with such documents, and educational use. Except as granted by CableLabs in a separate written license agreement, no license is granted to modify the documents herein (except via the Engineering Change process), or to use, copy, modify or distribute the documents for any other purpose.

This document may contain references to other documents not owned or controlled by CableLabs. Use and understanding of this document may require access to such other documents. Designing, manufacturing, distributing, using, selling, or servicing products, or providing services, based on this document may require intellectual property licenses from third parties for technology referenced in this document. To the extent this document contains or refers to documents of third parties, you agree to abide by the terms of any licenses associated with such third-party documents, including open source licenses, if any.

© Cable Television Laboratories, Inc. 2006-2017

DISCLAIMER

This document is furnished on an "AS IS" basis and neither CableLabs nor its members provides any representation or warranty, express or implied, regarding the accuracy, completeness, noninfringement, or fitness for a particular purpose of this document, or any document referenced herein. Any use or reliance on the information or opinion in this document is at the risk of the user, and CableLabs and its members shall not be liable for any damage or injury incurred by any person arising out of the completeness, accuracy, or utility of any information or opinion contained in the document.

CableLabs reserves the right to revise this document for any reason including, but not limited to, changes in laws, regulations, or standards promulgated by various entities, technology advances, or changes in equipment design, manufacturing techniques, or operating procedures described, or referred to, herein.

This document is not to be construed to suggest that any company modify or change any of its products or procedures, nor does this document represent a commitment by CableLabs or any of its members to purchase any product whether or not it meets the characteristics described in the document. Unless granted in a separate written agreement from CableLabs, nothing contained herein shall be construed to confer any license or right to any intellectual property. This document is not to be construed as an endorsement of any product or company or as the adoption or promulgation of any guidelines, standards, or recommendations.

Document Status Sheet

Document Control Number:	CL-SP-CANN-I16-170510																				
Document Title:	CableLabs' Assigned Names and Numbers																				
Revision History:	<table border="0"> <tr> <td>I01 - Released 01/19/07</td> <td>I10 - Released 07/29/14</td> </tr> <tr> <td>I02 - Released 03/06/08</td> <td>I11 - Released 12/18/14</td> </tr> <tr> <td>I03 - Released 08/11/09</td> <td>I12 - Released 03/19/15</td> </tr> <tr> <td>I04 - Released 02/12/10</td> <td>I13 - Released 05/15/15</td> </tr> <tr> <td>I05 - Released 02/10/11</td> <td>I14 - Released 03/17/16</td> </tr> <tr> <td>I06 - Released 11/17/11</td> <td>I15 - Released 01/11/17</td> </tr> <tr> <td>I07 - Released 08/09/12</td> <td>I16 - Released 05/10/17</td> </tr> <tr> <td>I08 - Released 11/13/12</td> <td></td> </tr> <tr> <td>I09 - Released 04/04/13</td> <td></td> </tr> </table>			I01 - Released 01/19/07	I10 - Released 07/29/14	I02 - Released 03/06/08	I11 - Released 12/18/14	I03 - Released 08/11/09	I12 - Released 03/19/15	I04 - Released 02/12/10	I13 - Released 05/15/15	I05 - Released 02/10/11	I14 - Released 03/17/16	I06 - Released 11/17/11	I15 - Released 01/11/17	I07 - Released 08/09/12	I16 - Released 05/10/17	I08 - Released 11/13/12		I09 - Released 04/04/13	
I01 - Released 01/19/07	I10 - Released 07/29/14																				
I02 - Released 03/06/08	I11 - Released 12/18/14																				
I03 - Released 08/11/09	I12 - Released 03/19/15																				
I04 - Released 02/12/10	I13 - Released 05/15/15																				
I05 - Released 02/10/11	I14 - Released 03/17/16																				
I06 - Released 11/17/11	I15 - Released 01/11/17																				
I07 - Released 08/09/12	I16 - Released 05/10/17																				
I08 - Released 11/13/12																					
I09 - Released 04/04/13																					
Date:	May 10, 2017																				
Status:	Work in Progress	Draft	Issued																		
			Closed																		
Distribution Restrictions:	Author Only	CL Member	CL Member/Vendor																		
			Public																		

Key to Document Status Codes:

- Work in Progress** An incomplete document, designed to guide discussion and generate feedback that may include several alternative requirements for consideration.
- Draft** A document in specification format considered largely complete, but lacking review by Members and vendors. Drafts are susceptible to substantial change during the review process.
- Issued** A generally public document that has undergone Member and Technology Supplier review, cross-vendor interoperability, and is for Certification testing if applicable. Issued Specifications are subject to the Engineering Change Process.
- Closed** A static document, reviewed, tested, validated, and closed to further engineering change requests to the specification through CableLabs.

Trademarks

CableLabs® is a registered trademark of Cable Television Laboratories, Inc. Other CableLabs marks are listed at <http://www.cablelabs.com/certqual/trademarks>. All other marks are the property of their respective owners.

Contents

1	SCOPE	7
1.1	Requirements	7
2	REFERENCES	8
2.1	Normative References	8
2.2	Informative References	8
2.3	Reference Acquisition	11
3	ABBREVIATIONS	12
4	CABLELABS DHCPv6 PROTOCOL FIELD REGISTRY	13
4.1	Definition	13
4.2	Format of the DHCPv6 CableLabs Vendor-specific Information Option	13
4.3	Template for defining new DHCPv6 CableLabs Vendor-specific Information Option codes	14
4.4	List of Relevant Specifications	15
5	CABLELABS XML REGISTRY	16
5.1	Guidelines	16
5.2	Examples	16
5.3	Registered XML name spaces	16
5.3.1	<i>DOCSIS</i>	16
5.3.2	<i>PacketCable</i>	18
5.3.3	<i>Stewardship and Fulfillment Interfaces</i>	19
5.3.4	<i>DPoE</i>	19
5.3.5	<i>Wireless</i>	19
6	CABLELABS DIAMETER AVP REGISTRY	20
6.1	Application Identifiers	20
6.1.1	<i>CableLabs-specific Application Identifiers</i>	20
6.2	Command Codes	20
6.2.1	<i>Command Codes Allocated for CableLabs</i>	20
6.3	Vendor Identifier	20
6.3.1	<i>CableLabs' Vendor Identifier</i>	20
6.4	Attribute-Value-Pair Codes	20
6.4.1	<i>CableLabs-specific AVP Codes</i>	20
6.5	Experimental Result Codes	22
6.5.1	<i>CableLabs-specific Experimental Result Codes</i>	22
6.6	Assignment of the Diameter Codes and Identifiers	22
6.6.1	<i>Application Identifiers</i>	22
6.6.2	<i>Command Codes</i>	22
6.6.3	<i>AVP Codes</i>	22
6.6.4	<i>Result Codes</i>	22
7	CABLELABS RCP REGISTRY	23
7.1	Definition	23
7.2	Format	23
7.3	Defining New Receive Channel Profiles	23
8	CABLELABS ASN.1 CODES REGISTRY	24
8.1	Definition	24
8.2	SMI Network Management Codes	24
8.2.1	<i>CableLabs Enterprise Number</i>	24
8.2.2	<i>CableLabs DOCSIS Project</i>	24

8.2.3	<i>CableLabs PacketCable Project</i>	25
8.2.4	<i>CableLabs OpenCable Project</i>	28
8.2.5	<i>CableLabs Wireless Project</i>	28
8.2.6	<i>CableLabs CableHome Project</i>	29
8.2.7	<i>CableLabs Security</i>	29
8.2.8	<i>CableLabs Common SMI MIB Modules</i>	29
9	CABLELABS APPLICATIONS REGISTRY	31
10	CABLELABS URN REGISTRY	32
10.1.1	<i>URLs and URN Namespaces Alignment</i>	33
11	DOCSIS PROVISIONING TLV NUMBER ASSIGNMENT REGISTRY	34
11.1	Top Level DOCSIS TLVs	34
11.2	TLV 5 Modem Capabilities Encoding sub-TLVs	36
11.3	TLV 43.5, 45, 65 L2VPN sub-TLVs	38
11.3.1	<i>TLV 43.5 L2VPN Encoding sub-TLVs</i>	38
11.3.2	<i>TLV 45 L2VPN DUT Filtering sub-TLVs</i>	41
11.3.3	<i>TLV 65 L2VPN MAC Aging sub-TLVs</i>	41
11.4	TLV 24/25/70/71 Service Flow sub-TLVs	41
11.4.1	<i>TLV 24 Service Flow sub-TLVs</i>	43
11.4.2	<i>TLV 25 Service Flow sub-TLVs</i>	43
11.5	TLV 22/23/60 Classification sub-TLVs	43
11.6	TLV 26 sub-TLVs	48
11.7	TLV 53, 54 DOCSIS sub-TLVs	49
11.8	TLV 72 MESP sub-TLVs	49
11.9	TLV 83 L2CP sub-TLVs	49
11.10	TLV 202 eRouter sub-TLVs.....	50
11.11	TLV 219 eTEA sub-TLVs.....	50
12	CABLELABS PNM REGISTRY	53
12.1	DOCSIS PNM Registry	53
12.1.1	<i>Definition</i>	53
12.1.2	<i>Format</i>	53
12.1.3	<i>CM PNM File Types</i>	53
12.1.4	<i>CCAP PNM File Types</i>	53
APPENDIX I	ACKNOWLEDGEMENTS	54
APPENDIX II	REVISION HISTORY (INFORMATIVE)	55
II.1	Engineering Changes for CL-SP-CANN-I02-080306	55
II.2	Engineering Change for CL-SP-CANN-I03-090811	55
II.3	Engineering Changes for CL-SP-CANN-I04-100212	55
II.4	Engineering Change for CL-SP-CANN-I05-110210	55
II.5	Engineering Change for CL-SP-CANN-I06-111117	55
II.6	Engineering Changes for CL-SP-CANN-I07-120809	55
II.7	Engineering Change for CL-SP-CANN-I08-121113	55
II.8	Engineering Change for CL-SP-CANN-I09-130404	56
II.9	Engineering Change for CL-SP-CANN-I10-140729	56
II.10	Engineering Changes for CL-SP-CANN-I11-141218	56
II.11	Engineering Changes for CL-SP-CANN-I12-150319	56
II.12	Engineering Changes for CL-SP-CANN-I13-150515	56
II.13	Engineering Changes for CL-SP-CANN-I14-160317	57
II.14	Engineering Changes for CL-SP-CANN-I15-170111	57
II.15	Engineering Changes for CL-SP-CANN-I16-170510	57

List of Tables

TABLE 1 - CABLELABS-SPECIFIC AVP CODES	21
TABLE 2 - CABLELABS ENTERPRISE NUMBER CODES	24
TABLE 3 - CABLELABS DOCSIS PROJECT CODES.....	24
TABLE 4 - CABLELABS PACKETCABLE PROJECT CODES.....	25
TABLE 5 - CABLELABS PACKETCABLE PROJECT ELECTRONIC SURVEILLANCE CODES.....	26
TABLE 6 - CABLELABS PACKETCABLE PROJECT ENHANCEMENTS CODES.....	26
TABLE 7 - CABLELABS PACKETCABLE PROJECT PACM CODES.....	26
TABLE 8 - CABLELABS PACKETCABLE PROJECT APPLICATION CODES.....	27
TABLE 9 - CABLELABS PACKETCABLE PROJECT SUPPORT CODES.....	27
TABLE 10 - CABLELABS PACKETCABLE PROJECT SUPPORT ELECTRONIC SURVEILLANCE CODES.....	27
TABLE 11 - CABLELABS PACKETCABLE PROJECT EUE CODES	28
TABLE 12 - CABLELABS PACKETCABLE PROJECT EUE DEVICE CODES	28
TABLE 13 - CABLELABS OPENCABLE PROJECT CODES	28
TABLE 14 - CABLELABS WIRELESS CODES	28
TABLE 15 - CABLELABS CABLEHOME CODES	29
TABLE 16 - CABLELABS SECURITY CODES	29
TABLE 17 - CABLELABS COMMON CODES	29
TABLE 18 - PACKETCABLE APPLICATION IDENTIFIERS	31
TABLE 19 - CABLELABS URN REGISTRY	32
TABLE 20 - CABLELABS DOCSIS CM PNM FILE TYPE CODES.....	53
TABLE 21 - CABLELABS DOCSIS CCAP PNM FILE TYPE CODES	53

1 SCOPE

This specification establishes a set of CableLabs registries and namespaces for Names and Numbers authoritatively assigned by CableLabs.

Numerous protocol fields make use of identifiers with well-known names or number values; for example, the IETF DHCP protocol and vendor-specific option values, the IETF RADIUS and DIAMETER protocols and associated CableLabs attributes, etc. To insure that such quantities have consistent values and interpretations in different implementations, their assignment must be administered by a central authority. For IETF protocols, that role is provided by the Internet Assigned Numbers Authority (IANA). For vendor-specific protocol fields that are defined by CableLabs specifications, or when the use of such protocol identifiers may be common to multiple CableLabs projects and specifications, this document defines a common repository to hold these values.

This document borrows some of the terminology and guidelines of IETF [RFC 2434].

The scope of this version of this specification includes:

- A DHCP registry for protocol fields authoritatively assigned by CableLabs that are in use in eDOCSIS, DOCSIS, CableHome, PacketCable, and OpenCable, for both IPv4 and DHCPv6.
- An XML registry for XML (URN, URL) namespaces for DOCSIS, PacketCable and Stewardship and Fulfillment Interfaces.
- A DIAMETER registry for PacketCable.
- A Receive Channel Profile (RCP) registry for CableLabs-defined Standard RCPs and Vendor-defined Manufacturer RCPs that are used in DOCSIS 3.0 and beyond to communicate the receiver capabilities of a cable modem.
- An ASN.1 Codes registry for CableLabs assigned MIBs.

1.1 Requirements

Throughout this document, the words that are used to define the significance of particular requirements are capitalized. These words are:

"MUST"	This word or the adjective "REQUIRED" means that the item is an absolute requirement of this specification.
"MUST NOT"	This phrase means that the item is an absolute prohibition of this specification.
"SHOULD"	This word or the adjective "RECOMMENDED" means that there may exist valid reasons in particular circumstances to ignore this item, but the full implications should be understood and the case carefully weighed before choosing a different course.
"SHOULD NOT"	This phrase means that there may exist valid reasons in particular circumstances when the listed behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
"MAY"	This word or the adjective "OPTIONAL" means that this item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because it enhances the product, for example; another vendor may omit the same item.

2 REFERENCES

2.1 Normative References

None.

2.2 Informative References¹

This specification uses the following informative references.

[802.1ad]	IEEE Std. 802.1ad-2005, IEEE Standard for Local and Metropolitan Area Networks – Virtual Bridged Local Area Networks Amendment 4: Provider Bridges, May 2006. Former amendment to 802.1Q, now part of 802.1Q-2011.
[802.1ah]	IEEE Std. 802.1ah-2008, IEEE Standard for Local and Metropolitan Area Networks – Virtual Bridged Local Area Networks – Amendment 6: Provider Backbone Bridges, January 2008. Former amendment to 802.1Q, now part of 802.1Q-2011. [802.1Q].
[CANN DHCP]	CableLabs' DHCP Options Registry, CL-SP-CANN-DHCP-Reg-I14-170111, January 11, 2017, Cable Television Laboratories, Inc.
[CCAP-OSSI]	Data-Over-Cable Service Interface Specifications, Converged Cable Access Platform Operations Support System Interface Specification, CM-SP-CCAP-OSSI-I08-151210, December 10, 2015, Cable Television Laboratories, Inc.
[CCAP-OSSIV3.1]	DOCSIS 3.1 CCAP Operations Support System Interface Specification, CM-SP-CCAP-OSSIV3.1-I09-170510, May 10, 2017, Cable Television Laboratories, Inc.
[CH CAP-MIB]	CableHome CAP MIB Specification, CH-SP-MIB-CAP-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[CH CDP-MIB]	CableHome CDP MIB Specification, CH-SP-MIB-CDP-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[CH CTP-MIB]	CableHome CTP MIB Specification, CH-SP-MIB-CTP-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[CH PSDEV-MIB]	CableHome PSDEV MIB Specification, CH-SP-MIB-PSDEV-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[CH QOS-MIB]	CableHome QOS MIB Specification, CH-SP-MIB-QOS-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[CH SEC-MIB]	CableHome Security MIB Specification, CH-SP-MIB-SEC-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[CM-OSSIV3.1]	Cable Modem Operations Support System Interface Specification, CM-SP-CM-OSSIV3.1-I09-170510, May 10, 2017, Cable Television Laboratories, Inc.
[CO CSA-MIB]	CableOffice Commercial Services Annex MIB Definition, CH-SP-CO-MIB-CSA-C01-060728, July 28, 2006, Cable Television Laboratories, Inc.
[DOCS TEST]	DOCSIS Testing MIB Specification, CM-SP-TestMIB-D06-121219, December 19, 2012, Cable Television Laboratories, Inc.
[DPoE-MULPIv2.0]	DOCSIS Provisioning of EPON Specifications, DPoE MAC and Upper Layer Protocols Specification, DPoE-SP-MULPIv2.0-I12-170510, May 10, 2017, Cable Television Laboratories, Inc.
[DPoE-OSSIV2.0]	DOCSIS Provisioning of EPON Specifications, DPoE Operations and Support System Interface Specification, DPoE-SP-OSSIV2.0-I11-170510, May 10, 2017, Cable Television Laboratories, Inc.

¹ Updated per CANN-N-14.0118-4 on 7/11/14 by PO; CANN-N-14.0123-1 on 9/25/14 and CANN-N-14.0124-1 on 12/12/14 by JB; CANN-N-15.0128 on 5/1/15 by PO.

[DPoG-MULPI]	DOCSIS Provisioning of GPON Specifications, DPoG MAC and Upper Layer Protocols Specification, DPoG-SP-MULPIv1.0-C01-160830, August 30, 2016, Cable Television Laboratories, Inc.
[DPoG-OSSI]	DOCSIS Provisioning of GPON Specifications, DPoG Operations and Support System Interface Specification, DPoG-SP-OSSIV1.0-C01-160830, August 30, 2016, Cable Television Laboratories, Inc.
[DSG]	DOCSIS Set-top Gateway (DSG) Interface Specification, CM-SP-DSG-I24-130808, August 8, 2013, Cable Television Laboratories, Inc.
[eDOCSIS]	eDOCSIS Specification, CM-SP-eDOCSIS-I28-150305, March 5, 2015, Cable Television Laboratories, Inc.
[eRouter]	IPv4 and IPv6 eRouter Specification, CM-SP-eRouter-I19-160923, September 23, 2016, Cable Television Laboratories, Inc.
[IANA AAA]	IANA's AAA parameters register: ftp://ftp.iana.org/assignments/aaa-parameters/
[IANA EN]	IANA's Enterprise-Numbers: http://www.iana.org/assignments/enterprise-numbers
[L2VPN]	Layer 2 Virtual Private Networks, CM-SP-L2VPN-I15-150528, May 28, 2015, Cable Television Laboratories, Inc.
[MIB-BB]	CableLabs Battery Backup MIB Specification, CL-SP-MIB-BB-I04-100608, June 8, 2010, Cable Television Laboratories, Inc.
[MIB-CLABDEF]	CableLabs Definition MIB Specification, CL-SP-MIB-CLABDEF-I12-160325, March 25, 2016, Cable Television Laboratories, Inc.
[M-OSSI]	Modular Operations Support System Interface Specification, CM-SP-M-OSSI-I08-081209, December 9, 2008, Cable Television Laboratories, Inc.
[MULPIv3.0]	DOCSIS 3.0 MAC and Upper Layer Protocols Interface Specification, CM-SP-MULPIv3.0-I30-170111, January 11, 2017, Cable Television Laboratories, Inc.
[OC MIB-HN]	OpenCable Home Networking MIB Specification, OC-SP-MIB-HN-I08-130530, May 30, 2013, Cable Television Laboratories, Inc.
[OC MIB-HOST2.X]	OpenCable Host Device 2.X MIB Specification, OC-SP-MIB-HOST2.X-I14-120531, May 31, 2012, Cable Television Laboratories, Inc.
[OC-DRI]	OpenCable Digital Receiver Interface Protocol, OC-SP-DRI-104-100910, September 10, 2010, Cable Television Laboratories, Inc.
[OLCA AUTH]	Online Content Access Authentication and Authorization Interface Specification, CL-SP-AUTH1.0-C01-160616, June 16, 2016, Cable Television Laboratories Inc.
[OSSI]	Operations Support System Interface Specification, SP-OSSI-C01-011119, November 19, 2001, Cable Television Laboratories, Inc.
[OSSIV1.1]	Operations Support System Interface Specification, CM-SP-OSSIV1.1-C01-050907, September 7, 2005.
[OSSIV2.0]	Data-Over-Cable Service Interface Specifications, Operations Support System Interface Specification, CM-SP-OSSIV2.0-C01-081104, November 4, 2008, Cable Television Laboratories Inc.
[OSSIV3.0]	DOCSIS 3.0 Operations Support System Interface Specification, CM-SP-OSSIV3.0-I30-170111, January 11, 2017, Cable Television Laboratories, Inc.
[PKT 29.229]	PacketCable 2.0 IMS Delta Specifications Cx/Dx Interfaces based on the Diameter Protocol Specification 3GPP TS 29.229, PKT-SP-29.229-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT ESP]	PacketCable Electronic Surveillance Specification, PKT-SP-ESP1.5-I02-070412, April 12, 2007, Cable Television Laboratories, Inc.
[PKT EUE-DATA]	PacketCable Management E-UE Provisioning Data Model Specification, PKT-SP-EUE-DATA C01-140314, March 14, 2014, Cable Television Laboratories, Inc.

[PKT EVE MIB1.5]	PacketCable Management Event MIB Specification, PKT-SP-EVEMIB1.5-I02-050812, August 12, 2005, Cable Television Laboratories, Inc.
[PKT MIB EXMTA1.5]	PacketCable MTA Extension MIB Specification, PKT-SP-MIB-EXMTA1.5-I01-050128, January 28, 2005, Cable Television Laboratories, Inc.
[PKT MIB EXSIG1.5]	PacketCable Signaling Extension MIB Specification, PKT-SP-MIB-EXSIG1.5-I05-121030, October 30, 2012, Cable Television Laboratories, Inc.
[PKT MIB MTA1.5]	PacketCable MTA MIB Specification, PKT-SP-MIB-MTA1.5-I01-050128, January 28, 2005, Cable Television Laboratories, Inc.
[PKT MIB SIG1.5]	PacketCable 1.5 Signaling MIB Specification, PKT-SP-MIB-SIG1.5-I01-050128, January 28, 2005, Cable Television Laboratories, Inc.
[PKT RST-EUE-PROV]	RST E-UE Provisioning Specification, PKT-SP-RST-EUE-PROV-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT SMA-PROV]	PacketCable Security, Monitoring, and Automation Provisioning Specification, PKT-SP-SMA-PROV-C01-130930, September 30, 2013, Cable Television Laboratories, Inc.
[PKT SP-RSTF]	PacketCable Residential SIP Telephony Feature Specification, PKT-SP-RSTF-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT UE-DATA]	PacketCable 2.0 UE Provisioning Data Model, PKT-SP-UE-DATA-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT UE-PROV]	PacketCable 2.0 UE Provisioning Framework, PKT-SP-UE-PROV-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT ACCT]	PacketCable Accounting Specification, PKT-SP-ACCT-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT ES-INF]	PacketCable Electronic Surveillance - Intra-Network Functions Specification, PKT-SP-ES-INF-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[PKT PROV]	PacketCable MTA Device Provisioning Specification, PKT-SP-PROV-C01-071129, November 29, 2007, Cable Television Laboratories, Inc.
[PKT PROV1.5]	PacketCable 1.5 MTA Device Provisioning Specification, PKT-SP-PROV1.5-I04-090624, June 24, 2009, Cable Television Laboratories, Inc.
[PKT RST-ACCT]	PacketCable Residential SIP Telephony Accounting Specification, PKT-SP-RST-ACCT-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.
[RFC 6289]	IETF RFC 6289, A Uniform Resource Name (URN) Namespace for CableLabs, June 2011.
[RFC 2141]	IETF RFC 2141, URN Syntax, May 1997.
[RFC 2434]	IETF RFC 2434/BCP0026, Guidelines for Writing an IANA Considerations Section in RFCs, October 1998.
[RFC 3261]	IETF RFC 3261, SIP: Session Initiation Protocol, June 2002.
[RFC 3315]	IETF RFC 3315, Dynamic Host Configuration Protocol for IPv6 (DHCPv6), July 2003.
[RFC 3495]	IETF RFC 3495, Dynamic Host Configuration Protocol (DHCP) Option for CableLabs Client Configuration, March 2003.
[RFC 3588]	IETF RFC 3588, Diameter Base Protocol, September 2003.
[RFC 5226]	IETF RFC 5266, Guidelines for Writing an IANA Considerations Section in RFCs, May 2008.
[RFC 6733]	IETF RFC 6733 Diameter Base Protocol, October 2012.
[R-OSSI]	Remote PHY OSS Interface Specification, CM-SP-R-OSSI-I06-170510, May 10, 2017, Cable Television Laboratories, Inc.
[RST-UE-PROV]	PacketCable RST UE Provisioning Specification, PKT-SP-RST-UE-PROV-C01-140314, March 14, 2014, Cable Television Laboratories, Inc.

[SAFI-CIP]	Campaign Information Package Specification, OC-SP-SaFI-CIPv3.0-I01-120307, March 7, 2012, Cable Television Laboratories, Inc.
[SAFI-COM]	Common Data Types Specification, OC-SP-SaFI-COMv3.0-I01-120307, March 7, 2012, Cable Television Laboratories, Inc.
[SAFI-IAF]	Interactive Application Fulfillment Summary Interface Specification, OC-SP-SaFI-IAFv3.0-I01-120307, March 7, 2012, Cable Television Laboratories, Inc.
[SAFI-IAM]	Interactive Application Messaging Specification, OC-SP-SaFI-IAMv3.0-I01-120307, March 7, 2012, Cable Television Laboratories, Inc.
[SAFI-SMS]	Service Measurement Summary Interface Specification, OC-SP-SaFI-SMSv3.0-I01-120307, March 7, 2012, Cable Television Laboratories, Inc.
[sRouter]	Standalone Router Specification, CL-SP-sRouter-I02-170111, January 11, 2017, Cable Television Laboratories, Inc.
[TEI]	TDM Emulation Interface Specification, CM-SP-TEI-I06-100611, June 11, 2010, Cable Television Laboratories, Inc.
[TR-069]	TR-069, CPE WAN Management Protocol v1.2, Issue 1 Amendment 4, July 2011, Broadband Forum Technical Report.
[TR-106]	TR-106, Data Model Template for TR-069-Enabled Devices, Issue 1, Amendment 6, July 2011, Broadband Forum Technical Report.
[WiFi MGMT]	WiFi Provisioning Framework Specification, WR-SP-WiFi-MGMT-I08-161213, December 13, 2016, Cable Television Laboratories, Inc.

2.3 Reference Acquisition

- Cable Television Laboratories, Inc., 858 Coal Creek Circle, Louisville, CO 80027; Phone +1-303-661-9100, Fax +1-303-661-9199; [http:// www.cablelabs.com](http://www.cablelabs.com).
- Internet Engineering Task Force (IETF) Secretariat, 48377 Fremont Blvd., Suite 117, Fremont, California 94538, USA; Phone: +1-510-492-4080, Fax: +1-510-492-4001; <http://www.ietf.org>.
- Internet Assigned Numbers Authority (IANA); <http://www.iana.org>.

3 ABBREVIATIONS ²

This document uses the following abbreviations and acronyms.

ASN.1	Abstract Syntax Notation 1
AVP	Attribute-Value Pairs
CCAP	Converged Cable Access Platform
DHCP	Dynamic Host Configuration Protocol
EPON	Ethernet Passive Optical Network
DOCSIS®	Data-Over-Cable Service Interface Specifications
DPoE™	DOCSIS Provisioning of EPON
DPoG™	DOCSIS Provisioning of GPON
IANA	Internet Assigned Numbers Authority
IETF	Internet Engineering Task Force
MIB	Management Information Base
NID	Namespace Identifier
PNM	Proactive Network Maintenance
RCC	Receive Channel Configurations
RCP	Receive Channel Profile
RFC	Request for Comments
SMA	Security, Monitoring, Automation
SNMP	Simple Network Management Protocol
URL	Uniform Resource Locator
URN	Uniform Resource Name
XML	Extensible Markup Language

² CANN-N-14.0123-1 on 9/25/14 by JB.

4 CABLELABS DHCP PROTOCOL FIELD REGISTRY

4.1 Definition

This document establishes the CableLabs DHCP registry and defines new name spaces associated with CableLabs DHCPv4 and DHCPv6 options:

- CableLabs project codes,
- Sub-option codes for DHCPv4 options,
- CableLabs Vendor-specific Information Option codes for DHCPv6.

The CableLabs Assigned Name and Number authority has established a registry of values for each of these name spaces which are found in [CANN DHCP].

4.2 Format of the DHCPv6 CableLabs Vendor-specific Information Option

DHCPv6 defines a Vendor-specific Information Option (see the option code `OPTION_VENDOR_OPTS` in section 22.17 of [RFC 3315]). This section defines the structure or format of the option data for the CableLabs Vendor-specific Information Option.

The format of the DHCPv6 CableLabs Vendor-specific Information option is:

```

  0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      OPTION_VENDOR_OPTS      |      option-len      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      enterprise-number (4491 for CableLabs)      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
.
.      CableLabs-defined option-data      .
.
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

option-code `OPTION_VENDOR_OPTS` (17)

option-len 4 + length of option-data field

enterprise-number The CableLabs' registered Enterprise Number:
4491, as registered with IANA in the Private
Enterprise Numbers:
<http://www.iana.org/assignments/enterprise-numbers.html>

CableLabs-defined
option-data An object containing one or more
CableLabs sub-options

The option-data field of the DHCPv6 CableLabs Vendor-specific Information option contains sub-option values. Each sub-option is structured as follows:

```

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   CableLabs sub-option-code   |   sub-option-len   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                               |                       |
|                               | (sub-option-len octets) |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

CableLabs sub-option-code:

```

0 1 2 3 4 5 6 7 0 1 2 3 4 5 6 7
+---+---+---+---+---+---+---+---+
| res |code | sub-option type  |
+---+---+---+---+---+---+---+---+

```

res: reserved for CableLabs, do not use; bits must be zero value.

code: identifies the CableLabs project code for this sub-option. The null value for these 3 bits ('000') identifies a generic DHCPv6 option that may be common to multiple projects. See the Values for the CableLabs Project Codes section of the CableLabs DHCP registry specification for the values of the CableLabs Project Codes for DHCPv6 options.

sub-option type: defines the option type.

sub-option-len length of sub-option-data field

sub-option-data the value of the CableLabs sub-option

4.3 Template for defining new DHCPv6 CableLabs Vendor-specific Information Option codes

Each request for a new definition of a DHCPv6 CableLabs Vendor-specific Information Option must include:

- A definition of the sub-option compliant with the format specified in this section.
- An Engineering Change Request against the CableLabs DHCP registry requesting the addition of the new option.

New DHCPv6 CableLabs Vendor-specific Information Option code must be defined using the following format:

```

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   CL-sub-option-code   |   sub-option-len   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
.                               .
.   CableLabs-defined sub-option-data   .
.                               .
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

CL-sub-option-code CL_OPTION_xxxxxxx where xxxxxxxx is descriptive name of the sub-option being defined.

Sub-option-len length of sub-option-data field

CableLabs-defined Sub-option-data	An object definition with normative requirements on how a DHCP client and server must use this information.
CableLabs Project	The requested CableLabs Project under which this new option should be assigned (a registered CableLabs Project code).

4.4 List of Relevant Specifications

The following list includes CableLabs and IETF specifications that contain definitions of DHCP option field values, or, references to the values defined in this document.

- CableLabs DHCP registry [CANN DHCP]
- DOCSIS OSSI specifications for DOCSIS 1.0 [OSSI], DOCSIS 1.1 [OSSIv1.1], DOCSIS 2.0 [OSSIv2.0]
- DOCSIS 3.0 MULPI [MULPIv3.0], OSSI [OSSIv3.0]
- DOCSIS 3.1 MULPI, OSSI [CM-OSSIv3.1], [CCAP-OSSIv3.1]
- PacketCable MTA Device Provisioning specifications version 1.0 [PKT PROV] and 1.5 [PKT PROV1.5]
- IETF [RFC 3495] and [RFC 6733]

5 CABLELABS XML REGISTRY

5.1 Guidelines

[RFC 6289] reserves and specifies a Uniform Resource Name (URN) Namespace Identifier (NID) of 'cablelabs' for use in CableLabs projects.

It is RECOMMENDED to define CableLabs URN namespaces according to [RFC 6289].

The goal of this section is to provide guidelines for the definition of new XML namespaces under CableLabs management and some recommendations to align the target namespaces and to allow consistent versioning.

It is RECOMMENDED to define CableLabs XML (URL) namespaces as follows:

Organization Identifier	Identifier	CableLabs Project Name	Version	Type of Document	Identifier	XSD Identifier
For CableLabs: www.cablelabs.com	namespaces	PacketCable DOCSIS CableHome	2.03.0	'DTD' 'XSD'	'smi' 'reg' 'ipdr' 'netconf'	e.g., CLAB-PACM-MIB

5.2 Examples

A few examples include:

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/>

<http://www.cablelabs.com/namespaces/PacketCable/2.0/xsd/smi/>

<urn:cablelabs:packetcable-example:ue:rst-sample>

5.3 Registered XML name spaces

The following name spaces are registered:

5.3.1 DOCSIS

5.3.1.1 *DOCSIS IPDR Service Definition Namespaces DOCSIS IPDR Service Definition Namespaces*³

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-SAMIS-TYPE-1>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-SAMIS-TYPE-2>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-CM-US-STATS-TYPE>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-CM-REG-STATUS-TYPE>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-TOPOLOGY-TYPE>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-SPECTRUM-MEASUREMENT-TYPE>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CPE-TYPE>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-DIAG-LOG-TYPE>

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-DIAG-LOG-EVENT-TYPE>

³ 3.1 namespaces added per CANN-N-15.0136-1 on 2/1/16 by KB.

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-DIAG-LOG-DETAIL-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-US-UTIL-STATS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-DS-UTIL-STATS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-CM-SERVICE-FLOW-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-IP-MULTICAST-STATS-TYPE>⁴
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-DS-OFDM-PROFILE-STATUS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-DS-OFDM-STATUS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-REG-STATUS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-SERVICE-FLOW-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-US-OFDMA-PROFILE-STATUS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-US-OFDMA-STATUS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-DS-OFDM-PROFILE-STATS-TYPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-US-OFDMA-PROFILE-STATS-TYPE>

5.3.1.2 DOCSIS Auxiliary Schema Namespaces⁵

<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CM>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CPE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-QOS>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-REC>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-CM-US>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-CM-NODE-CH>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-MD-NODE>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-SPECTRUM>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-DIAG-LOG>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-DIAG-LOG-DETAIL>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-US-UTIL>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-CMTS-DS-UTIL>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-SERVICE-FLOW>
<http://www.cablelabs.com/namespaces/DOCSIS/3.0/xsd/ipdr/DOCSIS-IP-MULTICAST>⁶
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-DS-OFDM>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-PARTIAL>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-CMTS-CM-US-OFDMA>
<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-OFDM-PROFILE>

⁴ Namespace row added per CANN-N-14.0120-1 on 10/1/14 by PO.

⁵ 3.1 namespaces added per CANN-N-15.0136-1 on 2/1/16 by KB.

⁶ Namespace row added per CANN-N-14.0120-1 on 10/1/14 by PO.

<http://www.cablelabs.com/namespaces/DOCSIS/3.1/xsd/ipdr/DOCSIS-SERVICE-FLOW>

5.3.1.3 DOCSIS CCAP YANG Namespaces

urn:cablelabs:params:xml:ns:yang:ccap

urn:cablelabs:params:xml:ns:yang:ccap:events

5.3.1.4 DOCSIS RPHY CCAP Core Namespaces⁷

urn:cablelabs:params:xml:ns:yang:rphy

urn:cablelabs:params:xml:ns:yang:rphy:events

5.3.2 PacketCable

5.3.2.1 PacketCable 2.0 PACM Namespaces

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/SMI/v1/CL-PKTC-UE>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/SMI/v1/CL-PKTC-User>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/SMI/v1/CL-PKTC-TC>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/v1/CL-PKTC-ACL>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/v1/CL-PKTC-BASE-SVC>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/SMI/v1/CL-PKTC-RST>

5.3.2.2 PacketCable 2.0 Auxiliary Namespaces

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/CLAB-DEF-MIB>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/SNMP-FRAMEWORK-MIB>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/SNMPv2-TC>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/SMI>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/SNMPv2-SMI>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/INET-ADDRESS-MIB>

<http://www.cablelabs.com/namespaces/PacketCable/R2/XSD/smi/SNMPv2-CONF>

5.3.2.3 PacketCable SMA Namespaces

urn:cablelabs:packetcable:sma:xsd:v1:instruction

urn:cablelabs:packetcable:sma:xsd:v1:event

urn:cablelabs:packetcable:sma:xsd:v1:reg

urn:cablelabs:packetcable:sma:xsd:v1:dereg

urn:cablelabs:packetcable:sma:xsd:v1:devprofile:response

urn:cablelabs:packetcable:sma:xsd:v1:devlist

urn:cablelabs:packetcable:sma:xsd:v1:heartbeat

urn:cablelabs:packetcable:sma:xsd:v1:smalogic

urn:cablelabs:packetcable:sma:xsd:v1:deviceprofile

urn:cablelabs:packetcable:sma:xsd:v1:cfgenv

⁷ Added per CANN-N-16.0144-1 on 11/21/16 by KB.

urn:cablelabs:packetcable:sma:xsd:v1:sig
urn:cablelabs:packetcable:sma:xsd:v1:ns
urn:cablelabs:packetcable:sma:xsd:v1:certs
urn:cablelabs:packetcable:sma:xsd:v1:base
urn:cablelabs:packetcable:sma:xsd:v1:op
urn:cablelabs:packetcable:sma:xsd:v1:ipv6cfg
urn:cablelabs:packetcable:sma:xsd:v1:ipv4cfg
urn:cablelabs:packetcable:sma:xsd:v1:mem

5.3.3 Stewardship and Fulfillment Interfaces

5.3.3.1 Stewardship and Fulfillment Interfaces Namespaces

<http://www.cablelabs.com/namespaces/safi/xsd/com>
<http://www.cablelabs.com/namespaces/safi/xsd/cip>
<http://www.cablelabs.com/namespaces/safi/xsd/iaf>
<http://www.cablelabs.com/namespaces/safi/xsd/iam>
<http://www.cablelabs.com/namespaces/safi/xsd/sms>

5.3.4 DPoE

5.3.4.1 DPoE 2.0 IPDR Service Definition Namespaces

<http://www.cablelabs.com/namespaces/DPOE/2.0/xsd/ipdr/DPOE-MEF-USAGE-TYPE>

5.3.4.2 DPoE 2.0 IPDR Auxiliary Schema Namespaces

<http://www.cablelabs.com/namespaces/DPOE/2.0/xsd/ipdr/DPOE-MEF-SERVICE-FLOW>

5.3.5 Wireless⁸

5.3.5.1 Wireless TR-181 Data Model Extensions Namespace

<http://www.cablelabs.com/namespaces/Wireless/TR181Ext>

⁸ Added per CANN-N-16.0148-2 on 11/21/16 by KB.

6 CABLELABS DIAMETER AVP REGISTRY

This section lists any IANA assigned CableLabs-specific DIAMETER applications and Command Codes, as well as CableLabs assigned DIAMETER protocol codes, including the Attribute-Value Pairs (AVP) and Experimental result codes.

For assignment of DIAMETER applications, command codes, AVP and result codes, please see the procedures in Section 6.6.

6.1 Application Identifiers

The Diameter applications are identified with the application identifiers as specified in [RFC 3588]. There are two kinds of applications: IETF standards track applications and vendor-specific applications. All application identifiers are assigned by [IANA AAA]. This chapter lists the application identifiers assigned by IANA to all CableLabs Diameter applications.

The application identifiers are transferred in Diameter command's header in the Application-ID field.

6.1.1 CableLabs-specific Application Identifiers

There are no CableLabs-specific application identifiers at this time.

6.2 Command Codes

The command codes are used for communicating the command associated with the Diameter message. The command code is carried in the Diameter header's Command-Code field. The command codes can be divided into standard command codes allocated by IANA and experimental command codes for testing purposes only.

6.2.1 Command Codes Allocated for CableLabs

There are no CableLabs-specific command codes at this time.

6.3 Vendor Identifier

The vendor identifier (also known as Enterprise number) indicates the vendor-specific attributes, result codes and application identifiers in Diameter commands. The vendor identifier is used in the Vendor-ID field of the AVP header and in the Vendor-ID AVP. The Vendor-ID AVP is used to identify the vendor in the Vendor-Specific-Application-Id and Experimental-Result-Code grouped AVPs.

6.3.1 CableLabs' Vendor Identifier

The IANA has allocated a vendor identifier value 4491 for CableLabs [IANA EN].

6.4 Attribute-Value-Pair Codes

The AVP codes are used together with the vendor identifier to identify each attribute uniquely. There are multiple AVP namespaces. The IETF IANA namespace, that is, the AVPs with vendor identifier zero or without vendor identifier, is controlled by IANA. Each vendor controls the AVP codes within his AVP namespaces.

6.4.1 CableLabs-specific AVP Codes

The CableLabs-specific AVPs have the Vendor-Specific bit ('V' bit) set in the AVP header and they carry the CableLabs' vendor identifier in the Vendor-ID field of the AVP header. The CableLabs-specific AVP codes are presented in the following table. AVP Names of "Obsolete" indicate that the AVP Code was previously assigned but is no longer used, and re-assignment of the AVP Code should be avoided.

Table 1 - CableLabs-specific AVP Codes

AVP Name	AVP Code	Specification Reference	Data Type	AVP Flag rules				
				Must	May	Should not	Must not	May Encr.
BCID	200	[PKT ES-INF]	UTF8String	V, M	P			N
Call-Transfer	201	[PKT RST-ACCT]	Group	V, M	P			N
Correlate-Reason	202	[PKT ES-INF]	Enumerated	V, M	P			N
Dialog-Id	203	[PKT ES-INF]	UTF8String	V, M	P			N
Digest-Algorithm	204	[PKT 29.229]	UTF8String	V			M	N
Digest-Auth-Param	205	[PKT 29.229]	OctetString	V			M	N
Digest-Domain	206	[PKT 29.229]	UTF8String	V			M	N
Digest-HA1	207	[PKT 29.229]	OctetString	V			M	N
Digest-QoP	208	[PKT 29.229]	UTF8String	V			M	N
Digest-Realm	209	[PKT 29.229]	UTF8String	V			M	N
Direction	210	[PKT ES-INF]	Enumerated	V, M	P			N
Direct-Message	211	[PKT ES-INF]	Enumerated	V, M	P			N
Element-ID	212	[PKT ES-INF]	UTF8String	V, M	P			N
Element-Type	213	[PKT ES-INF]	Enumerated	V, M	P			N
Event-Message-Type	214	[PKT ES-INF]	Enumerated	V, M	P			N
Location-Routing- Number	215	[PKT ACCT]	UTF8String	V, M	P			N
LRN-Source-Indicator	216	[PKT ACCT]	Integer32	V, M	P			N
LRN-Query-Status	217	[PKT ACCT]	Integer32	V, M	P			N
LI-Information	218	[PKT ES-INF]	Grouped	V, M	P			N
New-Dialog-Id	219	[PKT ES-INF]	UTF8String	V, M	P			N
NP-Data	220	[PKT ACCT]	Grouped	V, M	P			N
Obsolete (previously PCMM BCID)	221	[PKT ACCT]						
PCMM-Information	222	[PKT ACCT]	Grouped	V, M	P			N
Refer-To	223	[PKT RST-ACCT], [PKT ACCT]	UTF8String	V, M	P			N
RST-Information	224	[PKT RST-ACCT]	Grouped	V, M	P			N
RST-Subscriber-ID	225	[PKT RST-ACCT]	UTF8String	V, M	P			N
Server-Role	226	[PKT RST-ACCT]	Enumerated	V, M	P			N
Session-Type	227	[PKT RST-ACCT]	Enumerated	V, M	P			N
SIP-Digest-Authenticate	228	[PKT 29.229]	Grouped	V			M	N
SIP-Message	229	[PKT ES-INF]	OctetString	V, M	P			N
Target	230	[PKT RST-ACCT], [PKT ACCT]	UTF8String	V, M	P			N
Tap-Id	231	[PKT ES-INF]	UTF8String	V, M	P			N
Transfer-Session-Call-ID	232	[PKT RST-ACCT]	UTF8String	V, M	P			N

6.5 Experimental Result Codes

The Diameter answer messages must carry either Result-Code AVP or Experimental-Result AVP. The values of Result-Code AVP are controlled by IANA. The Experimental-Result AVP is a grouped AVP containing the Vendor-ID AVP and Experimental-Result-Code AVP, thus the experimental result codes are controlled in a vendor-specific manner.

6.5.1 CableLabs-specific Experimental Result Codes

There are no CableLabs-specific result codes at this time.

6.6 Assignment of the Diameter Codes and Identifiers

6.6.1 Application Identifiers

If a specification determines it will require a new application identifier based on the rules defined in [RFC 3588], a request for an application identifier should be sent to IANA. When the application identifier is received, an Engineering Change Request needs to be submitted against this document adding the newly assigned application identifier.

6.6.2 Command Codes

If a specification determines there is a need for a new command code(s) and no CableLabs allocated command code values are available, the procedures defined in [RFC 3588] need to be followed.

It should be noted that the standard command codes allocated for 3GPP are scarce resources and getting new ones would require IETF specification work to be done. Therefore it is recommended to use the existing command codes whenever possible.

Once a new command code is assigned, an Engineering Change Request should be submitted against this document adding the newly assigned command codes.

6.6.3 AVP Codes

If a specification determines a Diameter application needs new CableLabs-specific AVP code(s), an Engineering Change Request needs to be submitted against this document adding the newly assigned AVP code value. AVP codes are available on a first-come-first-serve basis and are assigned in numerical order. Skipping AVP code values is discouraged as is reserving blocks of AVP codes for further assignment. Given the possibility for multiple Engineering Change Requests assigning AVP codes at the same time, conflicts may occur. As such, AVP code values are only guaranteed to be unique and allocated once the Engineering Change Request becomes an Engineering Change Notice. To ensure unique AVP code values, oversight of the allocation process is required and the responsibility of the CableLabs employee currently responsible for this specification.

Re-use of the existing AVPs is recommended, but special attention should be paid to the use of enumerated AVPs. Defining new values for an enumerated AVP should be agreed to case by case with the specification group responsible for the particular enumerated AVP.

6.6.4 Result Codes

If a specification determines that a Diameter application needs new CableLabs-specific result code(s), an Engineering Change Request needs to be submitted against this document adding the newly assigned result code value. Result codes are available on a first-come-first-serve basis and are assigned in numerical order. Skipping result code values is discouraged as is reserving blocks of result codes for further assignment. Given the possibility for multiple Engineering Change Requests assigning result codes at the same time, conflicts may occur. As such, result code values are only guaranteed to be unique and allocated once the Engineering Change Request becomes an Engineering Change Notice. To ensure unique result code values, oversight of the allocation process is required and the responsibility of the CableLabs employee currently responsible for this specification.

7 CABLELABS RCP REGISTRY

7.1 Definition

This document establishes a CableLabs Receive Channel Profile (RCP) registry. RCPs are used by DOCSIS 3.0 cable modems to advertise their receiver capabilities. RCPs can be "Standard RCPs" defined by CableLabs (and existing in the CableLabs RCP namespace) or "Manufacturer RCPs" defined by the Manufacturer of a cable modem or cable modem silicon (and existing in the Manufacturer's RCP namespace).

DOCSIS 3.0 Cable Modem Termination Systems (CMTSs) support the cable operator configuration of Receive Channel Configurations (RCCs) based on the deployed downstream channel lineup and the details of a CM's receiver capabilities as described in an RCP encoding. Each RCC in the CMTS is indexed by the RCP-ID of the RCP upon which it is based. The CM itself may only advertise the RCP-ID, which is then used by the CMTS to match the CM to an appropriate RCC at Registration time. This registry provides the detailed RCP encoding associated with each RCP-ID to allow proper configuration of RCCs by the cable operator.

7.2 Format

Two encoding formats are defined for an RCP. The first is an XML encoding defined in [OSSIPv3.0], the second is a Type-Length-Value encoding defined in [MULPIv3.0]. The encoding format used for the CableLabs RCP registry is the XML format.

7.3 Defining New Receive Channel Profiles

Each request for a new entry in the CableLabs RCP registry must include the full XML encoding of the RCP, including an RCP-ID using either the CableLabs OUI (for a proposed new Standard RCP) or the Vendor's OUI (for a Manufacturer RCP), and an RCP Name.

8 CABLELABS ASN.1 CODES REGISTRY

8.1 Definition

This document establishes a CableLabs ASN.1 Codes registry. The purpose of this registry is to define a common repository for assignment of ASN.1 codes value of the type Object Identifier (OID) for CableLabs projects. Typically this registry contains the MIB Module Identities within the CableLabs enterprise branch for use within the Simple Network Management Protocol (SNMP), but can also contain any other ASN.1 definition used by other protocols or specifications.

8.2 SMI Network Management Codes

8.2.1 CableLabs Enterprise Number

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs (1.3.6.1.4.1.4491)

Table 2 - CableLabs Enterprise Number Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	clabFunction	CableLabs	[MIB-CLABDEF]
2	clabProject	CableLabs Projects	[MIB-CLABDEF]
3	clabSecurity	CableLabs Security	[MIB-CLABDEF]
4	clabCommonMibs	CableLabs common SMI information	[MIB-CLABDEF]

8.2.2 CableLabs DOCSIS Project ⁹

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjDociSis
(1.3.6.1.4.1.4491.2.1)

Table 3 - CableLabs DOCSIS Project Codes¹⁰

Decimal	Name	Description	References
0		Reserved for future use	
1	dsgMIB	DSG-MIB	
2	docsLoadBalanceMib	DOCS-LOADBAL-MIB	[OSSiv2.0]
3	dsgIfMIB	DSG-IF-MIB	[DSG]
4	dsgIfStdMib	DSG-IF-STD-MIB	[DSG]
5	docsIfExt2Mib	DOCS-IF-EXT2-MIB	[OSSiv2.0]
6	docsIfMCmtsMib	DOCS-IF-M-CMTS-MIB	[M-OSSI]
7	dtiMib	DTI-MIB	[M-OSSI]
8	docsL2vpnMIB	DOCS-L2VPN-MIB	[L2VPN]

⁹ CANN-N-14.0123-1 on 9/25/14 by JB

¹⁰ #25 and #26 added per CANN-N-14.0123-1 on 9/25/14 by JB; #27 added per CANN-N-14.0122-2 on 9/25/14 and CANN-N-14.0124-1 on 12/12/14 by JB; #28 added per CANN-N-15.0128-1 on 4/30/15 by PO; per CANN-N-16.0145-2 on 11/21/16 by KB.

Decimal	Name	Description	References
9	docsDiagMib	DOCS-DIAG-MIB	[OSSiv3.0]
10	docsSubmgt3Mib	DOCS-SUBMGT3-MIB	[OSSiv3.0]
11	docsSecMib	DOCS-SEC-MIB	[OSSiv3.0]
12	docsTestMIB	DOCS-TEST-MIB	[DOCS TEST]
13	sledMib	SLED-MIB	[eDOCSIS]
14	esafeMib	ESAFE-MIB	[eDOCSIS]
15	teaPwMIB	TEA-PW-MIB	[TEI]
16	teaPwTDMIB	TEA-PW-TDM-MIB	[TEI]
17	teaPwTcMIB	TEA-PW-TC-MIB	[TEI]
18	docsMcastMib	DOCS-MCAST-MIB	[OSSiv3.0]
19	docsMcastAuthMib	DOCS-MCAST-AUTH-MIB	[OSSiv3.0]
20	docsIf3Mib	DOCS-IF3-MIB	[OSSiv3.0]
21	docsQos3Mib	DOCS-QOS3-MIB	[OSSiv3.0]
22	docsLoadbal3Mib	DOCS-LOADBAL3-MIB	[OSSiv3.0]
23	docsDrfMib	DOCS-DRF-MIB	[M-OSSI]
24	ccapMib	CCAP-MIB	[CCAP-OSSI]
25	dpoeMIB	DOCS-DPOE-MIB	[DPoE-OSSiv2.0]
26	dpogMIB	DOCS-DPOG-MIB	[DPoG-OSSI]
27	docsPnmMIB	DOCS-PNM-MIB	[CM-OSSiv3.1]
28	docsIf31Mib	DOCS-IF31-MIB	[CM-OSSiv3.1], [CCAP-OSSiv3.1]
29	docsBpi2Ext31Mib	DOCS-BPI2EXT-MIB	[CM-OSSiv3.1]
30	docsRphyMib	DOCS-RPHY-MIB	[R-OSSI]

8.2.3 CableLabs PacketCable Project

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable
(1.3.6.1.4.1.4491.2.2)

Table 4 - CableLabs PacketCable Project Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcMtaMib	PKTC-MTA-MIB	[PKT MIB MTA1.5]
2	pktcSigMib	PKTC-SIG-MIB	[PKT MIB SIG1.5]
3	pktcEventMib	PKTC-EVENT-MIB	[PKT EVE MIB1.5]
4	pktcSecurity	PacketCable Security Node	[MIB-CLABDEF]
5	pktcLawfulIntercept	PacketCable Lawful intercept node	[MIB-CLABDEF]
6	pktcEnhancements	PacketCable Enhancements node	[MIB-CLABDEF]
7	pktcPACMMibs	PacketCable PACM node	[MIB-CLABDEF]

Decimal	Name	Description	References
8	pktcApplicationMibs	PacketCable Service node	[MIB-CLABDEF]
9	pktcSupportMibs	PacketCable Support node	[MIB-CLABDEF]
10	pktcEUEMibs	PacketCable EUE node	[MIB-CLABDEF]
11	pktcSMAMibs	PacketCable SMA node	[MIB-CLABDEF]

8.2.3.1 CableLabs PacketCable Project Lawful Intercept Codes

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.
pktcLawfulIntercept (1.3.6.1.4.1.4491.2.2.5)

Table 5 - CableLabs PacketCable Project Electronic Surveillance Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pcesp	PCESP	[PKT ESP]

8.2.3.2 CableLabs PacketCable Project Enhancements

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.
pktcEnhancements (1.3.6.1.4.1.4491.2.2.6)

Table 6 - CableLabs PacketCable Project Enhancements Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcEnMtaMib	PKTC-EN-MTA-MIB	[PKT MIB EXMTA1.5]
2	pktcEnSigMib	PKTC-EN-SIG-MIB	[PKT MIB SIG1.5]
3	pktcEnEventMib	Reserved for future use	
4	pktcEnSecurityMib	Reserved for future use	
5	pktcEnEUEMib	Reserved for future use	

8.2.3.3 CableLabs PacketCable Project PACM

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.
pktcPACMMibs (1.3.6.1.4.1.4491.2.2.7)

Table 7 - CableLabs PacketCable Project PACM Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcPACMTC	Reserved - withdrawn	
2	pktcPACMUEMib	Reserved - withdrawn	
3	pktcPACMUserMib	Reserved - withdrawn	
4		Reserved for future use	

Decimal	Name	Description	References
5		Reserved for future use	
6	pktcPACMMgtMIB	Reserved - withdrawn	
7	pktcPACMEventMib	Reserved - withdrawn	

CableLabs PacketCable Project Application

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.
pktcApplicationMibs (1.3.6.1.4.1.4491.2.2.8)

Table 8 - CableLabs PacketCable Project Application Codes

Decimal	Name	Description	References
0		Reserved for future use	
1		Reserved for future use	
2	pktcEUESTMIB	CL-PKTC-EUE-RST-MIB	[PKT RST-EUE-PROV]

8.2.3.4 CableLabs PacketCable Project Support

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.pkt
cSupportMibs (1.3.6.1.4.1.4491.2.2.9)

Table 9 - CableLabs PacketCable Project Support Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcESSupportMibs	PacketCable ES node	[MIB-CLABDEF]

8.2.3.4.1 CableLabs PacketCable Project Support Electronic Surveillance

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.pkt
cSupportMibs.pktcESSupportMibs (1.3.6.1.4.1.4491.2.2.9.1)

Table 10 - CableLabs PacketCable Project Support Electronic Surveillance Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcESTapMib	PKTC-ES-TAP-MIB	[PKT ES-INF]
2	pktcESIpTapMIB	PKTC-ES-IPTAP-MIB	[PKT ES-INF]

8.2.3.5 CableLabs PacketCable Project EUE

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.pkt
cEUEMibs (1.3.6.1.4.1.4491.2.2.10)

Table 11 - CableLabs PacketCable Project EUE Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcEUEDeviceMibs	PacketCable EUE Device node	[MIB-CLABDEF]
2	pktcEUETCMIB	CL-PKTC-EUE-TC-MIB	[PKT EUE-DATA]
3	pktcEUEDevMIB	CL-PKTC-EUE-DEV-MIB	[PKT EUE-DATA]
4	pktcEUEUserMIB	CL-PKTC-EUE-USER-MIB	[PKT EUE-DATA]
5	pktcEUEProvMgmtMIB	CL-PKTC-EUE-PROV-MGMT-MIB	[PKT EUE-DATA]
6	pktcEUEEventMIB	CL-PKTC-EUE-EVENT-MIB	[PKT EUE-DATA]
7	pktcEUEPrsMIB	CL-PKTC-EUE-PRS-MIB	[PKT EUE-DATA]

8.2.3.5.1 CableLabs PacketCable Project EUE Specific

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjPacketCable.pktcEUEMibs.pktcEUEDeviceMibs (1.3.6.1.4.1.4491.2.2.10.1)

Table 12 - CableLabs PacketCable Project EUE Device Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	pktcEDVAMIB	CL-PKTC-EUE-EDVA-MIB	[PKT RST-EUE-PROV]

8.2.4 CableLabs OpenCable Project

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjOpenCable (1.3.6.1.4.1.4491.2.3)

Table 13 - CableLabs OpenCable Project Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	ocStbHostMibModule	OC-STB-HOST-MIB	[OC MIB-HOST2.X]
2	ocHnMibModule	OC-HOME-NETWORK-MIB	[OC MIB-HN]

8.2.5 CableLabs Wireless Project

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjWireless (1.3.6.1.4.1.4491.2.5)

Table 14 - CableLabs Wireless Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	clabWIFIMib	CLAB-WIFI-MIB	[WiFi MGMT]

8.2.6 CableLabs CableHome Project

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabProject.clabProjCableHome
(1.3.6.1.4.1.4491.2.4)

Table 15 - CableLabs CableHome Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	cabhPsDevMib	CABH-PS-DEV-MIB	[CH PSDEV-MIB]
2	cabhSecMib	CABH-SEC-MIB	[CH SEC-MIB]
3	cabhCapMib	CABH-CAP-MIB	[CH CAP-MIB]
4	cabhCdpMib	CABH-CDP-MIB	[CH CDP-MIB]
5	cabhCtpMib	CABH-CTP-MIB	[CH CTP-MIB]
6	cabhQosMib	CABH-QOS-MIB Reserved	
7	cabhCsaMib	CABH-CSA-MIB	[CO CSA-MIB]
8	cabhQos2Mib	CABH-QOS2-MIB	[CH QOS-MIB]

8.2.7 CableLabs Security

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabSecurity (1.3.6.1.4.1.4491.3)

Table 16 - CableLabs Security Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	clabSecCertObject	Security Certificates node	[MIB-CLABDEF]
2	clabSecOlcaObject	OLCA Object Class	[MIB-CLABDEF] [OLCA AUTH]

8.2.8 CableLabs Common SMI MIB Modules¹¹

Prefix:

iso.org.dod.internet.private.enterprises.cableLabs.clabCommonMibs (1.3.6.1.4.1.4491.4)

Table 17 - CableLabs Common Codes

Decimal	Name	Description	References
0		Reserved for future use	
1	clabUpsMib	CLAB-UPS-MIB	[MIB-BB]
2	clabTopoMib	CLAB-TOPO-MIB	[OSSiv3.0]
3	clabGREMib	CLAB-GRE-MIB	[eRouter]
4	Reserved	Reserved	(formerly [eRouter], [sRouter])
5	Reserved	Reserved	(formerly [eRouter], [sRouter])

¹¹ Section 8.2.9 deleted per CANN-N-14.0123-1 on 9/24/14 by JB. Revised per CANN-N-14.0126-2 on 3/4/15 by JB; per CANN-N-15.0137-1, CANN-N-15.0139-3, CANN-N-16.0141-1 on 3/9/16 by kb; per CANN-N-16.0151-1 on 11/21/16 by KB.

Decimal	Name	Description	References
6	clabGWMib	CLAB-GW-MIB	[eRouter], [sRouter]
7	clabAniDevMib	CLAB-ANI-DEV-MIB	[sRouter]

9 CABLELABS APPLICATIONS REGISTRY

This section contains CableLabs assigned application identifiers, represented as unique integer values, to identify applications specified for cable clients. Each application identifier is accompanied by the CableLabs project specifying the application, the name of the application, an integer value representing the application identifier, and a reference specification. The principal use for application identifiers is within data definitions, such as MIB modules.

As an example, the PacketCable application identifier "1" represents the PacketCable RST application. Within PacketCable MIBs, it is used within the user MIB to associate specific users with the CableLabs RST application. Using the MIBs specified in [PKT EUE-DATA], specifically the MIB table pktcEUEUsrAppMapTable, the following row entries are of relevance:

pktcEUEUsrAppMapAppOrgID.<user A>.<application index>=4491 (identifies CableLabs)

pktcEUEUsrAppMapAppIdentifier.<user A>.<application index>=1 (identifies RST)

The above example specifies that user A is associated with the CableLabs specified application, RST.

The registry is specified in Table 18.

Table 18 - PacketCable Application Identifiers

Project	Application	Identifier	Reference Specification
PacketCable	Residential SIP Telephony (RST)	1	[PKT SP-RSTF]

10 CABLELABS URN REGISTRY

This section contains a registry for CableLabs URN namespaces. Not all CableLabs URNs are listed in this document as many could be part of projects that do not produce specifications, or would be difficult to maintain an up-to-date record in this document. However, projects are encouraged to list the leading part of the NSS (Namespace Specific String) [RFC 2141] with references to project names, URLs, or other type of references.

CableLabs URNs use the NID Namespace Identifier [RFC 2141] 'cablelabs' per [RFC 6289]. Some URN formatted namespaces and URIs are already defined in some XML namespaces defined in Section 4.

Table 19 shows registered URNs, or parts of them. Based on the [RFC 2141] URN definition this registry URNs structure is refined as follows to provide flexibility on the registration of URNs in Table 19:

<URN> ::= "urn:" <NID> ":" <projectNSSpart> ":" <subjectNSSpart> ":" <trailingNSSpart>

<NID> ::= 'cablelabs'

<projectNSSpart> per [RFC 2141] with the exception of ":"

<subjectNSSpart> := <NSS>; per [RFC 2141]; the subject of the URN

<trailingNSSpart> := <NSS>; per [RFC 2141]

While the URN above is the RECOMMENDED URN structure, other formats might be already being used. In such case only relevant parts of the URN are shown in Table 19. <trailingNSSpart> might be omitted in Table 19, refers to the reference for the complete list of URNs.

Table 19 - CableLabs URN Registry¹²

Project	<URN>	References
DOCSIS CCAP	urn:cablelabs:params:xml:ns:yang:ccap	[CCAP-OSSI]
DOCSIS CCAP	urn:cablelabs:params:xml:ns:yang:ccap:events	[CCAP-OSSI]
DOCSIS RPHY CCAP Core	urn:cablelabs:params:xml:ns:yang:rphy	[R-OSSI]
DOCSIS RPHY CCAP Core	urn:cablelabs:params:xml:ns:yang:rphy:events	[R-OSSI]
PacketCable	urn:cablelabs:packetcable:sma	[PKT SMA-PROV]
PacketCable	urn:cablelabs:packetcable:applications:rst	[PKT SP-RSTF]
PacketCable	urn:cablelabs:pktc2:oma	[PKT UE-PROV] [RST-UE-PROV]
OpenCable	urn:opencable-com:service:Tuner	[OC-DRI]
VoD Metadata		
Advertising and Interactive Services	urn:cablelabs:safi:xsd:cip:3.0	[SAFI-CIP]
Advertising and Interactive Services	urn:cablelabs:safi:xsd:com:3.0	[SAFI-COM]
Advertising and Interactive Services	urn:cablelabs:safi:xsd:iam:3.0	[SAFI-IAM]
Advertising and Interactive Services	urn:cablelabs:safi:xsd:iaf:3.0	[SAFI-IAF]
Advertising and Interactive Services	urn:cablelabs:safi:xsd:sms:3.0	[SAFI-SMS]
OLCA	urn:cablelabs:olca:1.0	[OLCA AUTH]

¹² Table updated per CANN-N-12.0115-1 on 3/19/13 by PO; per CANN-N-16.0144-1 on 11/21/16 by KB.

10.1 URLs and URN Namespaces Alignment

Section 4 listed a set of XML schema namespaces that may transition to URN as a future work revisions. The format of Section 4 is RECOMMENDED to define the entire URN structure for future defined URNs if applicable. To this effect, slash characters "/" of the format defined in Section 4.1 and shown in Section 4.2 are replaced with the character ":" with the exception of any trailing "/" which must be ignored.

11 DOCSIS PROVISIONING TLV NUMBER ASSIGNMENT REGISTRY¹³

This section contains the registry for all DOCSIS Provisioning TLV number assignments.

These TLVs are used in CM configuration files and in MAC Management messages. Currently these TLVs are used by one or more of the following specifications:

- DOCSIS specifications version 1.0, 1.1, 2.0, 3.0, 3.1
- DPoE specifications: v1.0, v2.0 (DPoE MULPI, DPoE MEF, DPoE SOAM)
- DPoG specifications: v1.0 (DPoG MULPI)
- DOCSIS family of specifications: L2VPN, TEI, DSG, eRouter, eDOCSIS

The way this chapter is organized is as follows: the first sections describe all the top level TLVs and the subsequent sections define the sub-TLV definitions for relevant top level TLVs.

11.1 Top Level DOCSIS TLVs¹⁴

Type	Description	Sub-TLV section	Spec Defined
0	Pad		DOCSIS 1.0
1	Downstream Frequency		DOCSIS 1.0
2	Upstream Channel ID		DOCSIS 1.0
3	Network Access Control Object		DOCSIS 1.0
4	DOCSIS 1.0 Class of Service		DOCSIS 1.0
5	Modem Capabilities Encoding	11.2	DOCSIS 1.0
6	CM Message Integrity Check (MIC)		DOCSIS 1.0
7	CMTS Message Integrity Check (MIC)		DOCSIS 1.0
8	Vendor ID Encoding		DOCSIS 1.0
9	SW Upgrade Filename		DOCSIS 1.0
10	SNMP Write Access Control		DOCSIS 1.0
11	SNMP MIB Object		DOCSIS 1.0
12	Modem IP Address		DOCSIS 1.0
13	Service(s) Not Available Response		DOCSIS 1.0
14	CPE Ethernet MAC Address		DOCSIS 1.0
15	Telephone Settings Option (deprecated)		DOCSIS 1.0
17	Baseline Privacy (Security)		DOCSIS 1.0
18	Max Number of CPEs		DOCSIS 1.0
19	TFTP Server Timestamp		DOCSIS 1.0
20	TFTP Server Provisioned Modem IPv4 Address		DOCSIS 1.0
21	SW Upgrade IPv4 TFTP Server		DOCSIS 1.0
22	Upstream Packet Classification	11.5	DOCSIS 1.1
23	Downstream Packet Classification	11.5	DOCSIS 1.1
24	Upstream SF	11.4	DOCSIS 1.1

¹³ Section added per CANN-N-14.0118-4 on 7/11/14 by PO; updated by CANN-N-14.0123-1 on 9/25/14 by JB.

¹⁴ Modified per CANN-N-16.0154-1 on 11/21/16 by KB; per CANN-N-17.0158-1 on 4/13/17 by KB.

Type	Description	Sub-TLV section	Spec Defined
25	Downstream SF	11.4	DOCSIS 1.1
26	Payload Header Suppression		DOCSIS 1.1
27	HMAC-Digest		DOCSIS 3.1
28	Maximum Number of Classifiers		DOCSIS 1.1
29	Privacy Enable		DOCSIS 1.1
30	Authorization Block		DOCSIS 1.1
31	Key Sequence Number		DOCSIS 1.1
32	Manufacturer Code Verification Certificate		DOCSIS 1.1
33	Co-Signer Code Verification Certificate		DOCSIS 1.1
34	SNMPv3 Kickstart Value		DOCSIS 1.1
35	Subscriber Mgmt Control		DOCSIS 1.1
36	Subscriber Mgmt CPE IPv4 List		DOCSIS 1.1
37	Subscriber Mgmt Filter Groups		DOCSIS 1.1
38	SNMPv3 Notification Receiver		DOCSIS 1.1
39	Enable 2.0 Mode		DOCSIS 2.0
40	Enable Test Modes		DOCSIS 2.0
41	Downstream Channel List		DOCSIS 2.0
42	Static Multicast MAC Address		DOCSIS 2.0
43	DOCSIS Extension Field	11.3.1	DOCSIS 1.0
44	Vendor Specific Capabilities		DOCSIS 1.0
45	Downstream Unencrypted Traffic (DUT) Filtering	11.3.2	DOCSIS 2.0
46	Transmit Channel Configuration (TCC)		DOCSIS 3.0
47	Service Flow SID Cluster Assignment		DOCSIS 3.0
48	Receive Channel Profile		DOCSIS 3.0
49	Receive Channel Configuration		DOCSIS 3.0
50	DSID Encodings		DOCSIS 3.0
51	Security Association Encoding		DOCSIS 3.0
52	Initializing Channel Timeout		DOCSIS 3.0
53	SNMPv1v2c Coexistence		DOCSIS 3.0
54	SNMPv3 Access View Configuration		DOCSIS 3.0
55	SNMP CPE Access Control		DOCSIS 3.0
56	Channel Assignment Configuration Settings		DOCSIS 3.0
57	CM Initialization Reason		DOCSIS 3.0
58	SW Upgrade IPv6 TFTP Server		DOCSIS 3.0
59	TFTP Server Provisioned Modem IPv6 Address		DOCSIS 3.0
60	Upstream Drop Packet Classification	11.5	DOCSIS 3.0
61	Subscriber Mgmt CPE IPv6 Prefix List		DOCSIS 3.0
62	Upstream Drop Classifier Group ID		DOCSIS 3.0
63	Subscriber Mgmt Control Max CPE IPv6 Prefix		DOCSIS 3.0
64	CMTS Static Multicast Session Encoding		DOCSIS 3.0
65	L2VPN MAC Aging Encoding	11.3.3	DOCSIS 2.0
66	Management Event Control Encoding		DOCSIS 3.0

Type	Description	Sub-TLV section	Spec Defined
67	Subscriber Mgmt CPE IPv6 Prefix List		DOCSIS 3.0
68	Default Upstream Target Buffer Configuration		DOCSIS 3.0
69	MAC Address Learning Control Encoding		DOCSIS 3.0
70	Upstream Aggregate Service Flow Encodings	11.4	DPoE 2.0
71	Downstream Aggregate Service Flow Encodings	11.4	DPoE 2.0
72	Metro Ethernet Service Profile	11.8	DPoE 2.0
73	Network Timing Profile		DPoE 2.0
74	Energy Management Parameter Encoding		DOCSIS 3.0
75	Energy Mgt. Mode Indicator		DOCSIS 3.1
76	Energy Mgt. Identifier List for CM		DOCSIS 3.1
77	DOCSIS Time Protocol Enable		DOCSIS 3.1
78	AQM Disable		DOCSIS 3.1
79	UNI Control Encoding		DOCSIS 3.0
80	Energy Management – DOCSIS Light Sleep Encodings		DOCSIS 3.1
81 ¹⁵	Manufacturer CVC Chain		DOCSIS 3.1
82	Co-signer CVC Chain		DOCSIS 3.1
83	L2CP Management		DPoE 2.0
84	Diplexer Band Edge		DOCSIS 3.1
201-231	eCM eSAFE Configuration File TLVs		
201	ePS		
202	eRouter	11.10	eRouter
203-215	Reserved		
216	eMTA		PacketCable 1.x
217	eSTB		DSG
218	Reserved		
219	eTEA	11.11	TEI
220	eDVA		PacketCable 2.0
221	eSG		SMA gateway
222-231	Reserved		
255	End-of-Data		DOCSIS 1.0

11.2 TLV 5 Modem Capabilities Encoding sub-TLVs¹⁶

Type	Description	Spec Defined
5	Modem Capabilities Encoding	
5.1	Concatenation Support	DOCSIS 1.1
5.2	DOCSIS Version	DOCSIS 1.1

¹⁵Type 81 and 82 added per CANN-N-14.0121-1 on 9/23/14 by JB.

¹⁶ 5.42.10 & 11 added per CANN-N-14.0123-1 on 9/25/14 by JB; modified per CANN-N-17.0158-1 on 4/13/17 by KB.

Type	Description	Spec Defined
5	Modem Capabilities Encoding	
5.3	Fragmentation Support	DOCSIS 1.1
5.4	Payload Header Suppression Support	DOCSIS 1.1
5.5	IGMP Support	DOCSIS 1.1
5.6	Privacy Support	DOCSIS 1.1
5.7	Downstream SAID Support	DOCSIS 1.1
5.8	Upstream Service Flow Support	DOCSIS 1.1
5.9	Optional Filtering Support	DOCSIS 1.1
5.10	Transmit Pre-Equalizer Taps	DOCSIS 1.1
5.11	Number of Transmit Pre-Equalizer Taps	DOCSIS 1.1
5.12	DCC Support	DOCSIS 1.1
5.13	IP Filters Support	DOCSIS 2.0
5.14	LLC Filters Support	DOCSIS 2.0
5.15	Expanded Unicast SID Space	DOCSIS 2.0
5.16	Ranging Hold-off Support	DOCSIS 2.0
5.17	L2VPN Capability	L2VPN
5.18	L2VPN eSAFE Host Capability	L2VPN
5.19	Downstream Unencrypted Traffic (DUT) Filtering	L2VPN
5.20	Upstream Frequency Range Support	DOCSIS 3.0
5.21	Upstream SC-QAM Symbol Rate Support	DOCSIS 3.0
5.22	Selectable Active Code Mode 2 Support	DOCSIS 3.0
5.23	Code Hopping Mode 2 Support	DOCSIS 3.0
5.24	Multiple Transmit SC-QAM Channel Support	DOCSIS 3.0
5.25	5.12 Msps Upstream Transmit SC-QAM Channel Support	DOCSIS 3.0
5.26	2.56 Msps Upstream Transmit SC-QAM Channel Support	DOCSIS 3.0
5.27	Total SID Cluster Support	DOCSIS 3.0
5.28	SID Clusters per Service Flow Support	DOCSIS 3.0
5.29	Multiple Receive SC-QAM Channel Support	DOCSIS 3.0
5.30	Total Downstream Service ID (DSID) Support	DOCSIS 3.0
5.31	Resequencing Downstream Service ID (DSID) Support	DOCSIS 3.0
5.32	Multicast Downstream Service ID (DSID) Support	DOCSIS 3.0
5.33	Multicast DSID Forwarding	DOCSIS 3.0
5.34	Frame Control Type Forwarding Capability	DOCSIS 3.0
5.35	DPV Capability	DOCSIS 3.0
5.36	Unsolicited Grant Service/Upstream Service Flow Support	DOCSIS 3.0
5.37	MAP and UCD Receipt Support	DOCSIS 3.0
5.38	Upstream Drop Classifier Support	DOCSIS 3.0
5.39	IPv6 Support	DOCSIS 3.0
5.40	Extended Upstream Transmit Power Capability	DOCSIS 3.0
5.41	Optional 802.1ad, 802.1ah, MPLS Classification Support	DOCSIS 3.0
5.42	D-ONU Capabilities	DPoE 1.0
5.42.1	DpoE/G Version Number	DPoE 1.0
5.42.2	Number of Unicast LLIDs	DPoE 1.0

Type	Description	Spec Defined
5	Modem Capabilities Encoding	
5.42.3	Number of Multicast LLIDs	DPoE 2.0
5.42.4	MESP Support	DPoE 2.0
5.42.5	Number of D-ONU Ports	DPoE 2.0
5.42.6	PON Data Rate Support	DPoE 2.0
5.42.7	Service OAM	DPoE 2.0
5.42.10	Number of T-CONTs Supported	DPoG 1.0
5.42.11	Total Number of (X)GEM Ports Supported	DPoG 1.0
5.43	Reserved	-
5.44	Energy Management Capabilities	DOCSIS 3.0
5.45	C-DOCSIS Capability Encoding	DOCSIS 3.0
5.46	CM-STATUS-ACK	DOCSIS 3.0
5.47	Energy Management Preferences	DOCSIS 3.1
5.48	Extended Packet Length Support Capability	DOCSIS 3.1
5.49	Multiple Receive OFDM Channel Support	DOCSIS 3.1
5.50	Multiple Transmit OFDMA Channel Support	DOCSIS 3.1
5.51	Downstream OFDM Profile Support	DOCSIS 3.1
5.52	Downstream OFDM channel subcarrier QAM modulation support	DOCSIS 3.1
5.53	Upstream OFDM channel subcarrier QAM modulation support	DOCSIS 3.1
5.54	Downstream Lower Band Edge Support	DOCSIS 3.1
5.55	Downstream Upper Band Edge Support	DOCSIS 3.1
5.56	Upstream Upper Band Edge Support	DOCSIS 3.1
5.57	DOCSIS Time Protocol Support	DOCSIS 3.1
5.58	DOCSIS Time Protocol Performance Support	DOCSIS 3.1
5.59	P _{max}	DOCSIS 3.1
5.60	Diplexer Downstream Lower Band Edge	DOCSIS 3.1
5.61	Diplexer Downstream Upper Band Edge	DOCSIS 3.1
5.62	Diplexer Upstream Upper Band Edge	DOCSIS 3.1

11.3 TLV 43.5, 45, 65 L2VPN sub-TLVs

11.3.1 TLV 43.5 L2VPN Encoding sub-TLVs¹⁷

Type	Description	Spec Defined
43.5	L2VPN Encoding	DOCSIS 3.0
43.5.1	VPN Identifier	L2VPN
43.5.2	NSI encapsulation format	DPoE 1.0
43.5.2.1	Other	DPoE 1.0
43.5.2.2	IEEE 802.1Q	DPoE 1.0
43.5.2.3	IEEE 802.1ad	DPoE 1.0
43.5.2.4	MPLS PW	DPoE 1.0
43.5.2.4.1	MPLS Pseudowire ID	DPoE 2.0

¹⁷ Added 43.5.27 per CANN-N-05.0131-1 by PO on 4/29/15; modified 43.5.16 per CANN-N-15.0139-3 on 3/9/16 by KB.

Type	Description	Spec Defined
43.5.2.4.2	MPLS Peer IP address	DPoE 2.0
43.5.2.4.3	Pseudowire Type	DPoE 1.0
43.5.2.4.4	MPLS Backup Pseudowire ID	DPoE 2.0
43.5.2.4.5	MPLS Backup Peer IP address	DPoE 2.0
43.5.2.5	L2TPv3 Peer	DPoE 1.0
43.5.2.6	IEEE 802.1ah Encapsulation	DPoE 1.0
43.5.2.6.1	IEEE 802.1ah Backbone Service Instance Tag (I-Tag) TCI	DPoE 1.0
43.5.2.6.2	IEEE 802.1ah Destination Backbone Edge Bridge (BEB) MAC Address (B-DA)	DPoE 1.0
43.5.2.6.3	16-bit value of [802.1ah] B-Tag TCI	DPoE 2.0
43.5.2.6.4	16-bit value of [802.1ah] I-Tag TPID	DPoE 2.0
43.5.2.6.5	3 bit I-PCP	DPoE 2.0
43.5.2.6.6	1 bit I-DEI	DPoE 2.0
43.5.2.6.7	1 bit I-UCA	DPoE 2.0
43.5.2.6.8	24-bit value of [802.1ah] I-SID Backbone Service Instance Identifier	DPoE 2.0
43.5.2.6.9	16-bit value of [802.1ah] B-Tag TPID	DPoE 2.0
43.5.2.6.10	1 bit B-PCP	DPoE 2.0
43.5.2.6.11	1 bit B-DEI	DPoE 2.0
43.5.2.6.12	12-bit value of [802.1ah] B-VID	DPoE 2.0
43.5.2.8	16-bit value of [802.1ad] S-TPID	DPoE 2.0
43.5.3	eSafe DHCP snooping	DPoE 1.0
43.5.4	CM Interface Mask subtype	L2VPN
43.5.5	Attachment Group ID (AGI)	DPoE 1.0
43.5.6	source attachment individual id (SAII)	DPoE 1.0
43.5.7	target attachment individual id (TAII)	DPoE 1.0
43.5.8	Upstream User Priority subtype	DPoE 1.0
43.5.9	Downstream User Priority Range	DPoE 1.0
43.5.10	L2VPN SA-Descriptor Subtypes	DPoE 1.0
43.5.43	Vendor Specific L2VPN Subtype	L2VPN
43.5.12	Pseudowire Type	DPoE 2.0
43.5.13	L2VPN Mode	DPoE 1.0
43.5.14	Tag Protocol Identifier (TPID) Translation	DPoE 1.0
43.5.14.1	Upstream TPID Translation	DPoE 1.0
43.5.14.2	Downstream TPID Translation	DPoE 1.0
43.5.14.3	Upstream S-TPID Translation	DPoE 1.0
43.5.14.4	Downstream S-TPID Translation	DPoE 1.0
43.5.14.5	Upstream B-TPID Translation	DPoE 1.0
43.5.14.6	Downstream B-TPID Translation	DPoE 1.0
43.5.14.7	Upstream I-TPID Translation	DPoE 1.0
43.5.14.8	Downstream I-TPID Translation	DPoE 1.0
43.5.15	L2CP Processing	DPoE 1.0/DPoE 2.0
43.5.15.1	L2CP Tunnel Mode	DPoE 1.0/DPoE 2.0
43.5.15.2	L2CP D-MAC Address	DPoE 1.0
43.5.15.3	L2CP L2PT D-MAC Address	DPoE 1.0/DPoE 2.0

Type	Description	Spec Defined
43.5.15.4	L2CP Filter	DPoE 2.0
43.5.16	Reserved (formerly DAC)	DPoE 2.0
43.5.18	Pseudowire Class	DPoE 2.0
43.5.19	Service Delimiter	DPoE 2.0
43.5.19.1	C-VID	DPoE 2.0
43.5.19.2	S-VID	DPoE 2.0
43.5.19.3	I-SID	DPoE 2.0
43.5.19.4	B-VID	DPoE 2.0
43.5.20	VSI Encoding	DPoE 2.0
43.5.20.1	VPLS Class	DPoE 2.0
43.5.20.2	E-Tree Role	DPoE 2.0
43.5.20.3	E-Tree Root VID	DPoE 2.0
43.5.20.4	E-Tree Leaf VID	DPoE 2.0
43.5.21	BGP Attribute	DPoE 2.0
43.5.21.1	BGP VPNID	DPoE 2.0
43.5.21.2	Route Distinguisher	DPoE 2.0
43.5.21.3	Route Target (import)	DPoE 2.0
43.5.21.4	Route Target (export)	DPoE 2.0
43.5.21.5	CE-ID or VE-ID	DPoE 2.0
43.5.22	VPN-SG Attribute	DPoE 2.0
43.5.23	Pseudowire Signaling	DPoE 2.0
43.5.24	L2VPN SOAM Subtype	L2VPN
43.5.24.1	MEP Configuration	L2VPN
43.5.24.1.1	MD Level	L2VPN
43.5.24.1.2	MD Name	L2VPN
43.5.24.1.3	MA Name	L2VPN
43.5.24.1.4	MEP ID	L2VPN
43.5.24.2	Remote MEP Configuration	L2VPN
43.5.24.2.1	MD Level	L2VPN
43.5.24.2.2	MD Name	L2VPN
43.5.24.2.3	MA Name	L2VPN
43.5.24.2.4	MEP ID	L2VPN
43.5.24.3	Fault Management Configuration	L2VPN
43.5.24.3.1	Continuity Check Messages	L2VPN
43.5.24.3.2	Enable Loopback Reply Messages	L2VPN
43.5.24.3.3	Enable Linktrace Messages	L2VPN
43.5.24.4	Performance Management Configuration	L2VPN
43.5.24.4.1	Frame Delay Measurement*	L2VPN
43.5.24.4.2	Frame Loss Measurement*	L2VPN
43.5.25	Network Timing Profile Reference	L2VPN
43.5.26	L2VPN DSID	L2VPN
43.5.27	Multipoint Enable/Disable	DPoE 2.0
43.5.254	L2VPN Error Encoding	L2VPN

Type	Description	Spec Defined
43.5.254.1	L2VPN Errored Parameter	L2VPN
43.5.254.2	L2VPN Confirmation Code	L2VPN
43.5.254.3	L2VPN Error Message Subtype	L2VPN

11.3.2 TLV 45 L2VPN DUT Filtering sub-TLVs

Type	Description	Spec Defined
45	Encoding for DUT Filtering	
45.1	Downstream Unencrypted Traffic (DUT) Control	DOCSIS 2.0
45.2	Downstream Unencrypted Traffic (DUT) CMIM	DOCSIS 2.0

11.3.3 TLV 65 L2VPN MAC Aging sub-TLVs

Type	Description	Spec Defined
65	L2VPN MAC Aging Encoding	
65.1	L2VPN MAC Aging Mode	DOCSIS 2.0

11.4 TLV 24/25/70/71 Service Flow sub-TLVs¹⁸

Type	Description	Spec Defined
24 25 70 71	Upstream Service Flow Downstream Service Flow Upstream Aggregate Service Flow Downstream Aggregate Service Flow	
24.1 25.1 70.1 71.1	Service Flow Reference or ASF Reference	DOCSIS 3.0
24.2 25.2	Service Flow Identifier	DOCSIS 3.0
24.3 25.3	Service Identifier	DOCSIS 3.0
24.4 25.4	Service Class Name	DOCSIS 3.0
24.5 25.5	Service Flow Error Encoding	DOCSIS 3.0
24.5.1 25.5.1	Errored Parameter	DOCSIS 3.0
24.5.2 25.5.2	Error Code	DOCSIS 3.0
24.5.3 25.5.3	Error Message	DOCSIS 3.0
24.6 25.6	Quality of Service Parameter Set Type	DOCSIS 3.0

¹⁸ Revised per CANN-N-14.0125-1 on 12/12/14 by JB.

Type	Description	Spec Defined
24.7 25.7	Traffic Priority	DOCSIS 3.0
24.8 25.8	Maximum Sustained Traffic Rate	DOCSIS 3.0
24.9 25.9	Maximum Traffic Burst	DOCSIS 3.0
24.10 25.10	Minimum Reserved Traffic Rate	DOCSIS 3.0
24.11 25.11	Assumed Minimum Reserved Rate Packet Size	DOCSIS 3.0
24.12 25.12	Timeout for Active QoS Parameters	DOCSIS 3.0
24.13 25.13	Timeout for Admitted QoS Parameters	DOCSIS 3.0
24.23 25.23	IP Type Of Service (DSCP) Overwrite	DOCSIS 3.0
24.27 25.27	Peak Traffic Rate	DOCSIS 3.0
24.31 25.31	Service Flow Required Attribute Mask	DOCSIS 3.0
24.32 25.32	Service Flow Forbidden Attribute Mask	DOCSIS 3.0
24.33 25.33	Service Flow Attribute Aggregation Rule Mask	DOCSIS 3.0
24.34 25.34	Application Identifier	DOCSIS 3.0
24.35 25.35	Buffer Control	DOCSIS 3.0
24.35.1 25.35.1	Minimum Buffer	DOCSIS 3.0
24.35.2 25.35.2	Target Buffer	DOCSIS 3.0
24.35.3 25.35.3	Maximum Buffer	DOCSIS 3.0
24.36 25.36 70.36 71.36	Aggregate Service Flow Reference	DOCSIS 3.0
24.37 25.37 70.37 71.37	Metro Ethernet Service Profile (MESP) Reference	DOCSIS 3.0
24.38 25.38	Serving Group Name	DOCSIS 3.0
24.40 25.40	AQM Encodings	DOCSIS 3.0
24.40.1 25.40.1	SF AQM Disable	DOCSIS 3.0
24.40.2 25.40.2	SF AQM Latency Target	DOCSIS 3.0

Type	Description	Spec Defined
24.41 25.41	Data Rate Unit Setting	DOCSIS 3.0
24.43 25.43	Vendor Specific QoS Parameters	DOCSIS 3.0
24.44 25.44	Service Flow Collection	DPoE 1.0

11.4.1 TLV 24 Service Flow sub-TLVs

Type	Description	Spec Defined
24	Upstream Service Flow	
24.14	Maximum Concatenated Burst	DOCSIS 3.0
24.15	Service Flow Scheduling Type	DOCSIS 3.0
24.16	Request/Transmission Policy	DOCSIS 3.0
24.17	Nominal Polling Interval	DPoE 1.0
24.18	Tolerated Poll Jitter	DOCSIS 3.0
24.19	Unsolicited Grant Size	DOCSIS 3.0
24.20	Nominal Grant Interval	DOCSIS 3.0
24.21	Tolerated Grant Jitter	DOCSIS 3.0
24.22	Grants per Interval	DOCSIS 3.0
24.24	Unsolicited Grant Time Reference	DOCSIS 3.0
24.25	Multiplier to Contention Request Backoff Window	DOCSIS 3.0
24.26	Multiplier to Number of Bytes Requested	DOCSIS 3.0

11.4.2 TLV 25 Service Flow sub-TLVs

Type	Description	Spec Defined
25	Downstream Service Flow	
25.14	Maximum Downstream Latency	DOCSIS 3.0
25.15	Reserved	-
25.17	Downstream Resequencing	DOCSIS 3.0

11.5 TLV 22/23/60 Classification sub-TLVs

Type	Description	Spec Defined
22 23 60	Upstream Classifier Downstream Classifier Upstream Drop Classifier (UDC)	
22.1 23.1 60.1	Classifier Reference	DOCSIS 3.0
22.2 23.2 60.2	Classifier Identifier	DOCSIS 3.0

Type	Description	Spec Defined
22 23 60	Upstream Classifier Downstream Classifier Upstream Drop Classifier (UDC)	
22.3 23.3 60.3	Service Flow Reference	DOCSIS 3.0
22.4 23.4 60.4	Service Flow Identifier	DOCSIS 3.0
22.5 23.5 60.5	Rule Priority	DOCSIS 3.0
22.6 23.6 60.6	Classifier Activation State	DOCSIS 3.0
22.7 23.7 60.7	Dynamic Service Change Action	DOCSIS 3.0
22.8 23.8 60.8	Classifier Error Encodings	DOCSIS 3.0
22.8.1 23.8.1 60.8.1	Errored Parameter	DOCSIS 3.0
22.8.2 23.8.2 60.8.2	Error Code	DOCSIS 3.0
22.8.3 23.8.3 60.8.3	Error Message	DOCSIS 3.0
22.9 23.9 60.9	IPv4 Packet Classification Encodings / TCP/UDP Packet Classification Encodings	DOCSIS 3.0
22.9.1 23.9.1 60.9.1	IPv4 Type of Service Range and Mask	DOCSIS 3.0
22.9.2 23.9.2 60.9.2	IP Protocol	DOCSIS 3.0
22.9.3 23.9.3 60.9.3	IPv4 Source Address	DOCSIS 3.0
22.9.4 23.9.4 60.9.4	IPv4 Source Mask	DOCSIS 3.0
22.9.5 23.9.5 60.9.5	IPv4 Destination Address	DOCSIS 3.0
22.9.6 23.9.6 60.9.6	IPv4 Destination Mask	DOCSIS 3.0
22.9.7 23.9.7 60.9.7	TCP/UDP Source Port Start	DOCSIS 3.0

Type	Description	Spec Defined
22 23 60	Upstream Classifier Downstream Classifier Upstream Drop Classifier (UDC)	
22.9.8 23.9.8 60.9.8	TCP/UDP Source Port End	DOCSIS 3.0
22.9.9 23.9.9 60.9.9	TCP/UDP Destination Port Start	DOCSIS 3.0
22.9.10 23.9.10 60.9.10	TCP/UDP Destination Port End	DOCSIS 3.0
22.10 23.10 60.10	Ethernet LLC Packet Classification Encodings	DOCSIS 3.0
22.10.1 23.10.1 60.10.1	Destination MAC Address	DOCSIS 3.0
22.10.2 23.10.2 60.10.2	Source MAC Address	DOCSIS 3.0
22.10.3 23.10.3 60.10.3	Ethertype/DSAP/Mac Type	DOCSIS 3.0
22.10.4 23.10.4 60.10.4	Slow Protocol Subtype	DOCSIS 3.0
22.11 23.11 60.11	IEEE 802.1P/Q Packet Classification Encodings	DOCSIS 3.0
22.11.1 23.11.1 60.11.1	IEEE 802.1P User Priority	DOCSIS 3.0
22.11.2 23.11.2 60.11.2	IEEE 802.1Q VLAN_ID	DOCSIS 3.0
22.12 23.12 60.12	IPv6 Packet Classification Encodings	DOCSIS 3.0
22.12.1 23.12.1 60.12.1	IPv6 Traffic Class	DOCSIS 3.0
22.12.2 23.12.2 60.12.2	IPv6 Flow Label	DOCSIS 3.0
22.12.3 23.12.3 60.12.3	IPv6 Next Header Type	DOCSIS 3.0
22.12.4 23.12.4 60.12.4	IPv6 Source Address	DOCSIS 3.0

Type	Description	Spec Defined
22 23 60	Upstream Classifier Downstream Classifier Upstream Drop Classifier (UDC)	
22.12.5 23.12.5 60.12.5	IPv6 Source Prefix Length (bits)	DOCSIS 3.0
22.12.6 23.12.6 60.12.6	IPv6 Destination Address	DOCSIS 3.0
22.12.7 23.12.7 60.12.7	IPv6 Destination Prefix Length (bits)	DOCSIS 3.0
22.13 23.13	CM Interface Mask (CMIM) Encoding	L2VPN
22.14 23.14 60.14	[IEEE 802.1ad] S-VLAN Packet Classification Encodings	DOCSIS 3.0
22.14.1 23.14.1 60.14.1	[IEEE 802.1ad] S-TPID	DOCSIS 3.0
22.14.2 23.14.2 60.14.2	[IEEE 802.1ad] S-VID	DOCSIS 3.0
22.14.3 23.14.3 60.14.3	[IEEE 802.1ad] S-PCP	DOCSIS 3.0
22.14.4 23.14.4 60.14.4	[IEEE 802.1ad] S-DEI	DOCSIS 3.0
22.14.5 23.14.5 60.14.5	[IEEE 802.1ad] C-TPID	DOCSIS 3.0
22.14.6 23.14.6 60.14.6	[IEEE 802.1ad] C-VID	DOCSIS 3.0
22.14.7 23.14.7 60.14.7	[IEEE 802.1ad] C-PCP	DOCSIS 3.0
22.14.8 23.14.8 60.14.8	[IEEE 802.1ad] C-CFI	DOCSIS 3.0
22.14.9 23.14.9 60.14.9	[IEEE 802.1ad] S-TCI	DOCSIS 3.0
22.14.10 23.14.10 60.14.10	[IEEE 802.1ad] C-TCI	DOCSIS 3.0
22.15 23.15 60.15	[IEEE 802.1ah] I-TAG Packet Classification Encodings	DOCSIS 3.0

Type	Description	Spec Defined
22 23 60	Upstream Classifier Downstream Classifier Upstream Drop Classifier (UDC)	
22.15.1 23.15.1 60.15.1	[IEEE 802.1ah] I-TPID	DOCSIS 3.0
22.15.2 23.15.2 60.15.2	[IEEE 802.1ah] I-SID	DOCSIS 3.0
22.15.3 23.15.3 60.15.3	[IEEE 802.1ah] I-TCI	DOCSIS 3.0
22.15.4 23.15.4 60.15.4	[IEEE 802.1ah] I-PCP	DOCSIS 3.0
22.15.5 23.15.5 60.15.5	[IEEE 802.1ah] I-DEI	DOCSIS 3.0
22.15.6 23.15.6 60.15.6	[IEEE 802.1ah] I-UCA	DOCSIS 3.0
22.15.7 23.15.7 60.15.7	[IEEE 802.1ah] B-TPID	DOCSIS 3.0
22.15.8 23.15.8 60.15.8	[IEEE 802.1ah] B-TCI	DOCSIS 3.0
22.15.9 23.15.9 60.15.9	[IEEE 802.1ah] B-PCP	DOCSIS 3.0
22.15.10 23.15.10 60.15.10	[IEEE 802.1ah] B-DEI	DOCSIS 3.0
22.15.11 23.15.11 60.15.11	[IEEE 802.1ah] B-VID	DOCSIS 3.0
22.15.12 23.15.12 60.15.12	[IEEE 802.1ah] B-DA	DOCSIS 3.0
22.15.13 23.15.13 60.15.13	[IEEE 802.1ah] B-SA	DOCSIS 3.0
22.16 23.16 60.16	ICMPv4/ICMPv6 Packet Classification Encodings	DOCSIS 3.0
22.16.1 23.16.1 60.16.1	ICMPv4/ICMPv6 Type Start	DOCSIS 3.0
22.16.2 23.16.2 60.16.2	ICMPv4/ICMPv6 Type End	DOCSIS 3.0

Type	Description	Spec Defined
22 23 60	Upstream Classifier Downstream Classifier Upstream Drop Classifier (UDC)	
22.17 23.17 60.17	MPLS Classification Encodings	DOCSIS 3.0
22.17.1 23.17.1 60.17.1	MPLS TC bits	DOCSIS 3.0
22.17.2 23.17.2 60.17.2	MPLS Label	DOCSIS 3.0
22.43 23.43 60.43	Vendor-specific Classifier Parameters	DOCSIS 3.0
23.43.5.1 60.43.5.1	VPN Identifier	DOCSIS 3.0
23.43.8 60.43.8	General Extension Information	DOCSIS 3.0

11.6 TLV 26 sub-TLVs

Type	Description	Spec Defined
26	Payload Header Suppression	
26.1	Classifier Reference	DOCSIS 3.0
26.2	Classifier Identifier	DOCSIS 3.0
26.3	Service Flow Reference	DOCSIS 3.0
26.4	Service Flow Identifier	DOCSIS 3.0
26.5	Dynamic Service Change Action	DOCSIS 3.0
26.6	Payload Header Suppression Error Encodings	DOCSIS 3.0
26.6.1	Errored Parameter	DOCSIS 3.0
26.6.2	Error Code	DOCSIS 3.0
26.6.3	Error Message	DOCSIS 3.0
26.7	Payload Header Suppression Field (PHSF)	DOCSIS 3.0
26.8	Payload Header Suppression Index (PHSI)	DOCSIS 3.0
26.9	Payload Header Suppression Mask (PHSM)	DOCSIS 3.0
26.10	Payload Header Suppression Size (PHSS)	DOCSIS 3.0
26.11	Payload Header Suppression Verification (PHSV)	DOCSIS 3.0
26.13	Dynamic Bonding Change Action	DOCSIS 3.0
26.43	Vendor Specific PHS Parameters	DOCSIS 3.0

11.7 TLV 53, 54 DOCSIS sub-TLVs

Type	Description	Spec Defined
53	SNMPv1v2c Coexistence Configuration	
53.1	SNMPv1v2c Community Name	DOCSIS 2.0
53.2	SNMPv1v2c Transport Address Access	DOCSIS 2.0
53.2.1	SNMPv1v2c Transport Address	DOCSIS 2.0
53.2.2	SNMPv1v2c Transport Address Mask	DOCSIS 2.0
53.3	SNMPv1v2c Access View Type	DOCSIS 2.0
53.4	SNMPv1v2c Access View Name	DOCSIS 2.0
54	SNMPv3 Access View Configuration	DOCSIS 2.0
54.1	SNMPv3 Access View Name	DOCSIS 2.0
54.2	SNMPv3 Access View Subtree	DOCSIS 2.0
54.3	SNMPv3 Access View Mask	DOCSIS 2.0
54.4	SNMPv3 Access View Type	DOCSIS 2.0

11.8 TLV 72 MESP sub-TLVs

Type	Description	Spec Defined
72	Metro Ethernet Service Profile Encoding	
72.1	MESP Reference	DPoE 2.0
72.2	MESP Bandwidth Profile (MESP-BP)	DPoE 2.0
72.2.1	MESP-BP Committed Information Rate	DPoE 2.0
72.2.2	MESP-BP Committed Burst Size	DPoE 2.0
72.2.3	MESP-BP Excess Information Rate	DPoE 2.0
72.2.4	MESP-BP Excess Burst Size	DPoE 2.0
72.2.5	MESP-BP Coupling Flag	DPoE 2.0
72.2.6	MESP-BP Color Mode	DPoE 2.0
72.2.6.1	MESP-BP-CM Color Identification Field	DPoE 2.0
72.2.6.2	MESP-BP-CM Color Identification Field Value	DPoE 2.0
72.2.7	MESP-BP Color Marking	DPoE 2.0
72.2.7.1	MESP-BP-CR Color Marking Field	DPoE 2.0
72.2.7.2	MESP-BP-CR Color Marking Field Value	DPoE 2.0
72.3	MESP Name	DPoE 2.0

11.9 TLV 83 L2CP sub-TLVs¹⁹

Type	Description	Spec Defined
83	L2CP Management	
83.1	CMIM	DPoE 2.0
83.2	L2CP Mode	DPoE 2.0
83.3	L2CP L2PT D-MAC Address	DPoE 2.0

¹⁹ Added per CANN-N-16.0154-1 on 11/21/16 by KB.

Type	Description	Spec Defined
83.4	L2CP Filter	DPoE 2.0

11.10 TLV 202 eRouter sub-TLVs²⁰

Type	Description	Spec Defined
202	eRouter Operation Mode encoding	
202.1	eRouter Initialization Mode Encoding	eRouter 1.0
202.2	TR-069 Management Server	eRouter 1.0
202.2.1	EnableCWMP	eRouter 1.0
202.2.2	URL parameter	eRouter 1.0
202.2.3	Username parameter	eRouter 1.0
202.2.4	Password parameter	eRouter 1.0
202.2.5	Connection Request Username	eRouter 1.0
202.2.6	Connection Request Password	eRouter 1.0
202.2.7	ACSOVERRIDE	eRouter 1.0
202.3	eRouter Initialization Mode Override	eRouter 1.0
202.10	Router Advertisement (RA) Transmission Interval	eRouter 1.0
202.11	SNMP MIB Object	eRouter 1.0
202.12	IP Multicast Configuration Server	eRouter 1.0
202.13	Link-ID Control	eRouter 1.0
202.42	Topology Mode Encoding	eRouter 1.0
202.43	Vendor Specific Information	eRouter 1.0
202.43.8	Vendor ID Encoding	eRouter 1.0
202.53	SNMPv1v2c Coexistence Configuration	eRouter 1.0
202.53.1	SNMPv1v2c Community Name	eRouter 1.0
202.53.2	SNMPv1v2c Community Name	eRouter 1.0
202.53.2.1	SNMPv1v2c Transport Address	eRouter 1.0
202.53.2.2	SNMPv1v2c Transport Address Mask	eRouter 1.0
202.53.2.3	SNMPv1v2c Access View Type	eRouter 1.0
202.53.2.4	SNMPv1v2c Access View Name	eRouter 1.0
202.54	SNMPv3 Access View Configuration	eRouter 1.0
202.54.1	SNMPv3 Access View Name	eRouter 1.0
202.54.2	SNMPv3 Access View Subtree	eRouter 1.0
202.54.3	SNMPv3 Access View Mask	eRouter 1.0
202.54.4	SNMPv3 Access View Type	eRouter 1.0

11.11 TLV 219 eTEA sub-TLVs

Type	Description	Spec Defined
219.8	eTEA Symbol Clock	CM-SP-TEI
219.9	eTEA IWF cfg-encoding	CM-SP-TEI

²⁰ Revised per CANN-N-15.0127-1 by JB on 3/4/15; updated per CANN-N-15.0132-1 on 5/1/15 by PO.

Type	Description	Spec Defined
219.9.1	eTEA PW Index Setting	CM-SP-TEI
219.9.2	eTEA Emulation Type	CM-SP-TEI
219.9.3	eTEA PW Peer Address	CM-SP-TEI
219.9.4	eTEA PW Peer Address IPv6	CM-SP-TEI
219.9.5	eTEA PW Destination Port	CM-SP-TEI
219.9.6	eTEA PW Peer Destination Port	CM-SP-TEI
219.9.7	eTEA PW Name	CM-SP-TEI
219.9.8	eTEA PW Description	CM-SP-TEI
219.9.9	eTEA PW Admin Status	CM-SP-TEI
219.9.10	eTEA Status Change Notification Enable	CM-SP-TEI
219.9.11	eTEA PW TDM Type	CM-SP-TEI
219.9.12	eTEA PW TDM Configuration Table Index	CM-SP-TEI
219.9.13	eTEA PW CESoPSNConfiguration Index	CM-SP-TEI
219.9.14	eTEA PW RTP SSRC	CM-SP-TEI
219.9.15	eTEA PW Peer SSRC	CM-SP-TEI
219.9.16	eTEA PW TDM Circulation Map	CM-SP-TEI
219.9.16.1	eTEA PW TDM Port #	CM-SP-TEI
219.9.16.2	eTEA PW TDM Timeslot Map	CM-SP-TEI
219.10	eTEA PW TDM configuration Table	CM-SP-TEI
219.10.1	eTEA PW TDM Configuration Table Index	CM-SP-TEI
219.10.2	eTEA PW TDM Payload Size	CM-SP-TEI
219.10.3	eTEA PW RTP header Used	CM-SP-TEI
219.10.5	eTEA jitter buffer setting	CM-SP-TEI
219.10.6	eTEA PW Payload Suppression	CM-SP-TEI
219.10.7	eTEA PW LOPS Exit Criteria	CM-SP-TEI
219.10.8	eTEA PW LOPS Entrance Criteria	CM-SP-TEI
219.10.10	eTEA PW Packet Replace Policy	CM-SP-TEI
219.10.11	eTEA PW Packet Loss Window	CM-SP-TEI
219.10.12	eTEA PW Excessive Loss Threshold	CM-SP-TEI
219.10.15	eTEA PW Severe Loss Threshold	CM-SP-TEI
219.10.16	eTEA PW RTP Timestamp Mode	CM-SP-TEI
219.10.17	eTEA PW Default Fill Pattern	CM-SP-TEI
219.10.18	eTEA PW L Flag Payload Policy	CM-SP-TEI
219.10.19	eTEA PW TOS	CM-SP-TEI
219.10.20	eTEA PW RTP Payload Type	CM-SP-TEI
219.10.21	eTEA PW RTP Peer Payload Type	CM-SP-TEI
219.10.22	eTEA PW RTP Timestamp Reference	CM-SP-TEI
219.10.23	eTEA PW RTP Peer Timestamp Reference	CM-SP-TEI
219.10.24	eTEA PW SRTP Enable	CM-SP-TEI
219.11	eTEA SNMP MIB Object	CM-SP-TEI
219.12	eTEA SNMP Write-Access Control	CM-SP-TEI
219.13	CESoPSN Configuration Table	CM-SP-TEI
219.13.1	PW CESoPSN Config Table Index	CM-SP-TEI

Type	Description	Spec Defined
219.13.2	Default Idle Pattern	CM-SP-TEI
219.13.3	LFlag Policy	CM-SP-TEI
219.13.4	RFlag Policy	CM-SP-TEI
219.13.5	Remote Defect Policy	CM-SP-TEI
219.13.6	LOPS Policy	CM-SP-TEI
219.13.7	App Sig TOS	CM-SP-TEI
219.13.8	RTP CAS PT	CM-SP-TEI
219.13.9	RTP CAS Peer PT	CM-SP-TEI
219.13.10	App Sig Idle	CM-SP-TEI
219.13.11	App Sig Interval	CM-SP-TEI
219.13.12	App Sig Max Interval	CM-SP-TEI
219.14	dsx1 Configuration Table	CM-SP-TEI
219.14.1	dsx1 port ID	CM-SP-TEI
219.14.2	dsx1 Line type	CM-SP-TEI
219.14.3	dsx1 Line Coding	CM-SP-TEI
219.14.4	dsx1 Circuit ID	CM-SP-TEI
219.14.5	dsx1 Loopback Configuration	CM-SP-TEI
219.14.6	dsx1 Signal Mode	CM-SP-TEI
219.14.7	dsx1 Transmit Clock Source	CM-SP-TEI
219.14.8	dsx1 Fdl	CM-SP-TEI
219.14.9	dsx1 Line Length	CM-SP-TEI
219.14.10	dsx1 Line Status Trap Enable	CM-SP-TEI
219.14.11	dsx1 Channelization	CM-SP-TEI
219.14.12	dsx1 Line Mode	CM-SP-TEI
219.14.13	dsx1 Line Build Out	CM-SP-TEI
219.43	eTEA Vendor Specific Extensions	CM-SP-TEI
219.255	eTEA End of Text	CM-SP-TEI

12 CABLELABS PNM REGISTRY²¹

This section defines a Proactive Network Maintenance (PNM) File Type Registry.

12.1 DOCSIS PNM Registry

12.1.1 Definition

This document establishes a CableLabs DOCSIS Proactive Network Maintenance (PNM) File Type Registry. PNM File Types are associated with PNM tests implemented in the CM or CCAP. PNM tests generate files to report measurements or test results. Refer to the Proactive Network Maintenance Object Model section of [CCAP-OSSIV3.1] and the Proactive Network Maintenance Requirements section of [CM-OSSIV3.1] for further details.

12.1.2 Format

The PNM File Type format is a four-byte hexadecimal identifier specific to the type of CCAP or CM PNM test that generated the data file. The first three bytes (0x504E4D) of the file type are encoded as the ASCII Hex values for the ASCII string “PNM”. The fourth byte is encoded as a unique file type identifier, e.g., 0x01, 0x02, ..., 0xFF.

12.1.3 CM PNM File Types

The CM PNM File Type identifiers are defined in the number range 0x01 to 0x64.

Table 20 - CableLabs DOCSIS CM PNM File Type Codes

CM PNM Test	File Identifier
Symbol Capture	504E4D01
OFDM Channel Estimate Coefficient	504E4D02
Downstream Constellation Display	504E4D03
Receive Modulation Error Ratio (RxMER)	504E4D04
Downstream Histogram	504E4D05
Upstream Pre-equalizer Coefficients	504E4D06
Upstream Pre-equalizer Coefficients Last Update	504E4D07
OFDM FEC Summary	504E4D08
Spectrum Analysis	504E4D09
OFDM Modulation Profile	504E4D0A

12.1.4 CCAP PNM File Types

The CCAP PNM File Type identifiers are defined in the number range 0x65 to 0xFF.

Table 21 - CableLabs DOCSIS CCAP PNM File Type Codes

CCAP PNM Test	File Identifier
Symbol Capture	504E4D65
Active and Quiet Probe	504E4D66
Impulse Noise	504E4D67
Histogram	504E4D68
Receive Modulation Error Ratio (RxMER)	504E4D69
Triggered Spectrum Capture	504E4D6A

²¹ Section added per CANN-N-17.0156-1

Appendix I Acknowledgements

On behalf of CableLabs and its participating member companies, we would like to extend our thanks to all member and vendor participants who contributed to the development of the protocol fields registered in this specification. Key contributors to this document are recognized individually in each of the CableLabs project-specific specifications.

Steve Burroughs - CableLabs

Appendix II Revision History (Informative)

II.1 Engineering Changes for CL-SP-CANN-I02-080306

The following engineering changes are incorporated into CL-SP-CANN-I02-080306:

ECN	Date Accepted	Summary
CANN-N-07.0028-3	7/25/2007	Registration of additional Diameter AVPs for PacketCable 2.0
CANN-N-07.0029-2	7/18/2007	Update to DIAMETER Registrations
CANN-N-07.0033-2	11/28/2007	New Section CableLabs ASN.1 Codes Registry
CANN-N-07.0036-3	2/20/2008	Addition of application registry

II.2 Engineering Change for CL-SP-CANN-I03-090811

The following engineering change is incorporated into CL-SP-CANN-I03-090811:

ECN	Date Accepted	Summary
CANN-N-08.0038-2	1/28/2009	Modifications to support SMA devices

II.3 Engineering Changes for CL-SP-CANN-I04-100212

The following engineering changes are incorporated into CL-SP-CANN-I04-100212:

ECN	Date Accepted	Summary
CANN-N-09.0045-1	11/11/2009	SAFI namespace update
CANN-N-09.0046-1	12/16/2009	Home Networking Addition

II.4 Engineering Change for CL-SP-CANN-I05-110210

The following engineering change is incorporated into CL-SP-CANN-I05-110210:

ECN	Date Accepted	Summary
CANN-N-10.0091-1	1/5/2011	New OID for Online Content Access Project

II.5 Engineering Change for CL-SP-CANN-I06-111117

The following engineering change is incorporated into CL-SP-CANN-I06-111117:

ECN	Date Accepted	Summary
CANN-N-11.0099-2	10/05/2011	Addition of cmapMib to CableLabs DOCSIS Project Codes

II.6 Engineering Changes for CL-SP-CANN-I07-120809

The following engineering changes are incorporated into CL-SP-CANN-I07-120809:

ECN	Date Accepted	Summary
CANN-N-12.0110-4	7/11/2012	Add support for RFC6289 and reserve CCAP YANG namespace
CANN-N-12.0112-1	6/13/2012	Definition of Wireless project in and TR-069 registry in the CANN spec

II.7 Engineering Change for CL-SP-CANN-I08-121113

The following engineering change is incorporated into CL-SP-CANN-I08-121113:

ECN	Date Accepted	Summary
CANN-N-12.0111-2	10/17/12	URN namespace registry for CANN spec

II.8 Engineering Change for CL-SP-CANN-I09-130404

The following engineering change is incorporated into CL-SP-CANN-I09-130404:

ECN	Date Accepted	Summary	Author
CANN-N-12.0115-1	12/12/12	Correction to CANN-N-12.0111-2	Sundaresan

II.9 Engineering Change for CL-SP-CANN-I10-140729

The following engineering change is incorporated into CL-SP-CANN-I10-140729:

ECN	Date Accepted	Summary	Author
CANN-N-14.0118-4	5/14/14	New Chapter for DOCSIS TLV reservation	Sundaresan

II.10 Engineering Changes for CL-SP-CANN-I11-141218

The followings engineering changes are incorporated into CL-SP-CANN-I11-141218

ECN	Date Accepted	Summary	Author
CANN-N-14.0120-1	8/13/2014	Add new DOCSIS schema namespaces	Barringer
CANN-N-14.0121-1	10/15/2014	Security CVC Chain TLV Numbers for CANN	Lopez
CANN-N-14.0122-2	10/15/2014	New project code for DOCSIS PNM MIB	Alvarez
CANN-N-14.0123-1	10/1/2014	Updates for DPoX	Burroughs
CANN-N-14.0124-1	11/26/2014	Add reference for 3.1 DOCSIS CM OSSl specification	Alvarez
CANN-N-14.0125-1	12/03/2014	Reserve DPoE SF Collection TLVs	Burroughs

II.11 Engineering Changes for CL-SP-CANN-I12-150319

The followings engineering changes are incorporated into CL-SP-CANN-I12-150319

ECN	Date Accepted	Summary	Author
CANN-N-14.0126-2	2/11/2015	Update CANN spec to add OID prefix for eRouter Tunneling MIBs	Berg
CANN-N-15.0127-1	2/11/2015	Adding eRouter TLVs 53 & 54 to CANN	Kloberdans

II.12 Engineering Changes for CL-SP-CANN-I13-150515

The followings engineering changes are incorporated into CL-SP-CANN-I13-150515.

ECN	Date Accepted	Summary	Author
CANN-N-15.0128-1	4/15/2015	Add DOCSIS project code for IF31 MIB	Sundelin
CANN-N-15.0131-1	4/15/2015	DPoE Multipoint sub-TLV Assignment	Burroughs
CANN-N-15.0132-1	4/29/2015	Add newly defined TLV 202 sub-types to CANN specification	Berg

II.13 Engineering Changes for CL-SP-CANN-I14-160317

The followings engineering changes are incorporated into CL-SP-CANN-I14-160317.

ECN	Date Accepted	Summary	Author
CANN-N-15.0136-1	12/9/2015	Create new namespaces for DOCSIS 3.1 schemas	Barringer
CANN-N-15.0137-1	12/16/2015	Add GRE and MAP MIBs to SMI Network Management Codes in CANN	Berg
CANN-N-15.0139-3	2/24/2016	Retire and reserve the DAC TLV	Burroughs
CANN-N-16.0141-1	2/24/2016	Update MIB Module Names	Hedstrom

II.14 Engineering Changes for CL-SP-CANN-I15-170111

The followings engineering changes are incorporated into CL-SP-CANN-I15-170111.

ECN	Date Accepted	Summary	Author
CANN-N-16.0143-1	4/6/2016	Update TLV Registry for L2CP Processing	Burroughs
CANN-N-16.0144-1	4/20/2016	Reservation of RPHY YANG namespace	Hedstrom
CANN-N-16.0145-2	4/27/2016	Addition of DOCS-RPHY-MIB OID	Hedstrom
CANN-N-16.0148-2	6/30/2016	Update Wireless TR-069 Data Model Registry	Burroughs
CANN-N-16.0151-1	7/21/2016	Reserve Deprecated SMI Numbers	Burroughs
CANN-N-16.0154-1	8/25/2016	Add Top Level L2CP TLV	Burroughs

II.15 Engineering Changes for CL-SP-CANN-I16-170510

The followings engineering changes are incorporated into CL-SP-CANN-I16-170510.

ECN	Date Accepted	Summary	Author
CANN-N-17.0156-1	3/9/2017	Addition of PNM Test Types	Hedstrom
CANN-R-17.0158-1	4/13/2017	CANN EC to accompany MULPI diplexer configuration EC	Dolas